

# River Team 2010

Winter Presentation



Owner

A

E

C

L

S



David



Urszula



Joanna



Brent



Nima



Martin






Sebastian



Alex

# Site Conditions

University building in Weimar, Germany



A

E


C

L


S

# Flooding Challenge


detailed terrain profile and different water levels



Normal water level



33 year flood



100 year flood

A

E

C

L

S


# Big Idea: Transparency

Showing interior processes and actions



Inspiration: **Bauhaus**

University Building in Dessau by Walter Gropius, 1919



- innovation
- **visual communication**
- **no barriers** between students and profs
- functionality / simplicity

Our goals:

- NO: naive copy of the building
- YES: use the way of **thinking**

A

E

C

L

S

# 3D views



A

E

South view  
West facade



C

L

S

# Plan +1 Ground Floor

North ↑


A

E

C

L

S




stairs and ramp

- Faculty Offices
- Dept. Chair's Office
- Admin. Offices
- Faculty Lounge
- Student Offices
- Auditorium
- Large Classrooms
- Small Classrooms
- Seminar Rooms
- Instructional Labs
- Server Room
- Technical Support
- Storage Room
- Restroom
- Additional




# Plan +2 Second Floor




# Plan +3 Third Floor

North ↑



- Faculty Offices
- Depart. Chair's Office
- Admin. Offices
- Faculty Lounge
- Student Offices
- Auditorium
- Large Classrooms
- Small Classrooms
- Seminar Rooms
- Instructional Labs
- Server Room
- Technical Support
- Storage Room
- Restroom
- Additional



A

E



C

L

S




# Sections



A

E

North-South  
through cantilevered auditorium



C

L

S

West-East  
through atrium (vertical circulation) and auditorium

# Loading Considerations

## Gravity Loads

### DEAD LOADS:


MEP	5 psf
CLADDING	20 psf
MISC	12 psf
SELF-WEIGHT	80 to 100 psf

### LIVE LOADS:

ROOF	20 psf
SNOW	9 psf
GREEN ROOF	25 psf
CLASSROOM	50 psf
OFFICE	50 psf
AUDITORIUM	60 psf
LABORATORY ROOM	100 psf
<b>CORRIDOR</b>	<b>100 psf</b>
STORAGE	120 psf
PARTITIONS	20 psf

## Lateral Loads

### Later Load Distribution




Average wind load = 12 mph  
Design wind load = 60 mph  
**Solution = Lateral Braces & Shear Walls**

# Soil Considerations

High Water Table

Bearing capacity 8000 psf


Excavation needed



# Structural Steel Transparency



## L-Shaped



### Foundation:

**Square Footing (8' x 8')**  
**2 Layers of No. 9 bars @ 6" (Bottom)**  
**2 Layer of No. 3 bars @ 18" (top)**

### Typical Member Sizes

**Beam: W16 x67**

**Girder: W18x71**

**Column: W12 x 40**

**Composite Floor System:**  
**3" decking + 3" LWC slab**

**Lateral System:**  
**HSS21/2"x1/2"x1/4"**

A

E

C

L


S

# Structural Steel Transparency




A

## Ground Floor



Typical Bay Size: 24' x 12.5'



Max Bay Size: 29' x 29'

E

C



L

S

# Structural Steel Transparency



## Second Floor



A

E

C

L



S

# Structural Steel Transparency



A

## Third & Roof Floor



E

C

L

S

# Reinforced Concrete Transparency



A

## Typical Member

Floor: 5"


Column: 14"

Beam: 14" x 20"

Girder: 12" x 20"

Shear Wall: 10" x 6'

Foundation: 10'  
Square Spread



E

C

L

S




# Reinforced Concrete Transparency



## Grid Layout

Largest Bay Size

29' x 22'



A

E

C

L

S

# Reinforced Concrete Transparency




A  
E  
C  
L  
S

## First Floor

- Column
- Beam
- Girder
- Bearing Walls

Cantilever: 24" x 50"



# Reinforced Concrete Transparency




A  
E  
C  
L  
S

## Second Floor

- Column
- Beam
- Girder
- Bearing Walls

**Auditorium**  
Span: 50' Long  
18"x32" Beams  
every 10'




# Reinforced Concrete Transparency



A  
E  
C  
L  
S

## Third Floor

- Column
- Beam
- Girder
- Bearing Walls




# Reinforced Concrete Transparency



A

## Wind Load

- Diaphragm Action
- Shear Walls Carry Load



E

C

L



S

# Reinforced Concrete Transparency



## Cantilever Load Path

- Large Moment Reaction
- Requires beam 24"x50"
- 13 #10 bars
- Wall at 50" long has tension component of 700 kips.



A

E

C

L

S

# Structural Comparison

Transparency



A

E

C

L

S

Slab

RC Depth: 20"

SS Depth: 18"


Floor to floor: 13'6"

Floor to ceiling

**System**


**Advantages**

**Disadvantages**



Lightweight,  
Shorter Depth

Expensive



Cheap,  
Thermal Mass

Schedule,  
Larger  
members



MEP

**MEP: 24"**


# Site Layout Transparency




Recycling

**Storage:**  
▪ Storage: 4000 SF  
▪ Earth: 2300 SF

- Offices
- Trailers
- Toilets
- Storage container (tools)



Signs (stop, warnings)



▪ 25 Parking lots (4000 SF)

A  
E  
C  
L  
S




# Site Layout Transparency



A

## Normal Water Level

E



C

L

S


# Site Layout Transparency



A

## 33 Year Flood

E



C

L


S

# Second Big Idea Inspiration

## Historical buildings

### Features

- Symmetry
- Simple mass
  - Detail




### Harmony and Proportions

- Function
- Structure
  - Form

# Big Idea: ReUse

How do we understand it?

- reusing the **historical style**  
(composition)
- reusing **old materials**  
(from existing building – sustainability)
- reusing the **water**  
(gathering rain water)
- “reusing” **sunlight**  
(ex. light shelves)
- reusing **rooms**  
(flexibility of spaces)




# General Idea



## Building Mass

### Formal goals:


- **symmetry** in plan
- **axes**
- atrium – focal **core** area
- **historical** facade feeling



- view to the river and parc
- cantilevered auditorium
- modern structure



Modularity in plan  
(reuse of "ad quadratum"  
idea)



A  
E  
C  
L  
S

# Façade Explorations



Start:  
Historical building...




..use symmetry!



..booring...

..too monumental...




Final: decision



..put it together!

..go back to symmetry!

Schulhaus Eichi  
Ort: Niederglatt  
Architekt: Lüthi + Partner AG




..make it modern!



..no more symmetry!

..play with it!







..messy...



..look for inspirations!


A  
E  
C  
L  
S

# Façade ReUse



# Plan +1

North ↑




- Faculty Offices
- Dept. Chair's Office
- Admin. Offices
- Faculty Lounge
- Student Offices
- Auditorium
- Large Classrooms
- Small Classrooms
- Seminar Rooms
- Instructional Labs
- Server Room
- Technical Support
- Storage Room
- Restroom
- Additional


A vertical bar on the right side of the plan, divided into colored sections: yellow (A), grey (E), grey (C), grey (L), and grey (S). The letters A, E, C, L, and S are placed to the right of their respective sections.



# Plan +2



- Faculty Offices
- Dept. Chair's Office
- Admin. Offices
- Faculty Lounge
- Student Offices
- Auditorium
- Large Classrooms
- Small Classrooms
- Seminar Rooms
- Instructional Labs
- Server Room
- Technical Support
- Storage Room
- Restroom
- Additional




MAIN ENTRANCE BRIDGE


MAIN HALL

ATRIUM

North



# Plan +3



- Faculty Offices
- Depart. Chair's Office
- Admin. Offices
- Faculty Lounge
- Student Offices
- Auditorium
- Large Classrooms
- Small Classrooms
- Seminar Rooms
- Instructional Labs
- Server Room
- Technical Support
- Storage Room
- Restroom
- Additional

North ↑

A



E

C

L

S

# 3D Views



A


E

C

L



S

# Sections ReUse




N-S, through entrance bridge and auditorium cantilevering over the river

W-E, through atrium core (vertical circulation)



A  
E  
C  
L  
S

# The Signature Spiral ReUse



Core area

A

E

C


L

S

# Structural Steel ReUse



## Square Shape – Steel frame



### Foundation:

Square Footing (10' x 10')  
2 Layers of No. 9 bars @ 6" (Bottom)  
2 Layer of No. 3 bars @ 18" (top)

### Typical Member Sizes

Beam: W14x30

Girder: W16x77

Column: W14x61

Composite Floor System:  
3" deck + 3.5" LWC Slab

Lateral System:  
HSS2"x2"x1/4"

A

E

C

L


S

# Structural Steel ReUse



A

## Ground Floor



E

C

L

S



# Structural Steel ReUse



A

Second Floor

Max Bay Size: 50' x 19'



E

C

L

Typical Bay Size: 19' x 25'

S





# Structural Steel ReUse




Third Floor

Typical Bay Size: 19' x 19'



Max Bay Size: 50' x 25' (sloped)





A  
E  
C  
L  
S

# Structural Alternative Reuse

Roof Floor

Typical Bay Size: 19' x 25'




Max Bay Size: 50' x 25'

A  
E  
C  
L  
S

# Structural Steel ReUse



Staircase Solution (NS X-section)



Floating Staircase

A

E

C


L

S

# Structural Steel ReUse



## Cantilever Auditorium Solution (EW X-section)



A  
E  
C  
L  
S

# Reinforced Concrete ReUse



## Typical Member

Floor: 6"


Column: 18"

Beam: 16" x 25"

Girder: 10" x 25"

Shear Wall: 10" x 6'

Foundation: 10'  
Square Spread



A

E

C

L


S

# Reinforced Concrete ReUse



## Grid Layout

Largest Bay Size  
25' x 33'



A

E

C

L


S

# Reinforced Concrete ReUse



## First Floor

- Column
- Beam
- Girder
- Bearing Walls



A

E

C


L

S

# Structural System

## Second Floor

- Column
- Beam
- Girder
- Bearing Walls



A

E

C

L


S



# Structural System

## Third Floor

- Column
- Beam
- Girder
- Bearing Walls



A

E

C


L

S

# Structural System

## Cantilever Load Path

- Large Moment Reaction
- Requires beam 24"x68"
- 14 #10 bars
- Wall at 68" long has tension component of 966 kips.




# Reinforced Concrete ReUse



## Overturning Moment

Check Under Most Extreme Case



A

E

C

L

S

# Reinforced Concrete ReUse





## Comparison

Floor to floor: 13'6"

Slab

RC Depth: 25" SS Depth: 16"


	System	Advantages	Disadvantages
Floor to ceiling		Lightweight, Shorter Depth, Balance Cantilevers	Expensive
MEP		Cheap, Historic Material	Schedule, Difficult Cantilever

MEP: 24"



A  
E  
C  
L  
S

# Site Layout Concrete Option - ReUse




A

- Offices
- Trailers
- Toilets
- Storage container (tools)

- Storage:**
- Rebar: 1400 SF
  - Formwork: 2200 SF
  - Earth: 2300 SF

Recycling

E




C

Signs (stop, warnings)

L

- 25 Parking lots (4000 SF)



S

# Site Layout


Concrete Option - ReUse



A

## Normal Water Level

E



C

L

S

# Site Layout Concrete Option - ReUse



A


## 33 Year Flood

E


C

L

S



# Site Layout Steel Option - ReUse



A

E

C


L

S

- Storage:
- Steel: 1400 SF
- Steel: 1900 SF
- Earth: 2200 SF

- Offices
- Trailers
- Toilets
- Storage container (tools)
- Recycling

- 25 Parking lots (5000 SF)





# Site Layout Steel Option - ReUse



A


E

C

L

S

## Normal Water Level



Movement of Mobile-crane for the heaviest lift

# Site Layout Steel Option - ReUse



A


E

C


L

S

## 33 Year Flood



# General Issues



A




E

C

L

S

# General Issues



A


E

C

L

S

# Equipment



A

E



- **Alternative fuels:** Biodiesel, Dimethyletheris (DME): close to CO2 neutral
- **95% of the machine recyclable**
- **Reduced external sound levels**
- **Rental:** 2 miles from site
- 1 excavator, 1 Mini excavator, 2 Dumpers



C



Transport: 15 miles  
Excavation: 90 000 CF  
Duration of task: 10 days

L

S




- **Mobile crane: Liebherr LTM 1160 5.1**  
Capacity at 180 ft: 1,7 tons – Concrete  
Capacity at 150 ft: 3,7 tons – Steel  
Heaviest lift: steel structure: 2,8 tons
- **Concrete pump:** Radius 35 FT
- **Pilling rig**

	ISO	DIN	ISO	DIN	ISO	DIN	ISO	DIN	ISO	DIN
1	100	100	100	100	100	100	100	100	100	100
2	110	110	110	110	110	110	110	110	110	110
3	120	120	120	120	120	120	120	120	120	120
4	130	130	130	130	130	130	130	130	130	130
5	140	140	140	140	140	140	140	140	140	140
6	150	150	150	150	150	150	150	150	150	150
7	160	160	160	160	160	160	160	160	160	160
8	170	170	170	170	170	170	170	170	170	170
9	180	180	180	180	180	180	180	180	180	180
10	190	190	190	190	190	190	190	190	190	190
11	200	200	200	200	200	200	200	200	200	200
12	210	210	210	210	210	210	210	210	210	210
13	220	220	220	220	220	220	220	220	220	220
14	230	230	230	230	230	230	230	230	230	230
15	240	240	240	240	240	240	240	240	240	240
16	250	250	250	250	250	250	250	250	250	250
17	260	260	260	260	260	260	260	260	260	260
18	270	270	270	270	270	270	270	270	270	270
19	280	280	280	280	280	280	280	280	280	280
20	290	290	290	290	290	290	290	290	290	290
21	300	300	300	300	300	300	300	300	300	300
22	310	310	310	310	310	310	310	310	310	310
23	320	320	320	320	320	320	320	320	320	320
24	330	330	330	330	330	330	330	330	330	330
25	340	340	340	340	340	340	340	340	340	340
26	350	350	350	350	350	350	350	350	350	350
27	360	360	360	360	360	360	360	360	360	360
28	370	370	370	370	370	370	370	370	370	370
29	380	380	380	380	380	380	380	380	380	380
30	390	390	390	390	390	390	390	390	390	390
31	400	400	400	400	400	400	400	400	400	400
32	410	410	410	410	410	410	410	410	410	410
33	420	420	420	420	420	420	420	420	420	420
34	430	430	430	430	430	430	430	430	430	430
35	440	440	440	440	440	440	440	440	440	440
36	450	450	450	450	450	450	450	450	450	450
37	460	460	460	460	460	460	460	460	460	460
38	470	470	470	470	470	470	470	470	470	470
39	480	480	480	480	480	480	480	480	480	480
40	490	490	490	490	490	490	490	490	490	490
41	500	500	500	500	500	500	500	500	500	500
42	510	510	510	510	510	510	510	510	510	510
43	520	520	520	520	520	520	520	520	520	520
44	530	530	530	530	530	530	530	530	530	530
45	540	540	540	540	540	540	540	540	540	540
46	550	550	550	550	550	550	550	550	550	550
47	560	560	560	560	560	560	560	560	560	560
48	570	570	570	570	570	570	570	570	570	570
49	580	580	580	580	580	580	580	580	580	580
50	590	590	590	590	590	590	590	590	590	590
51	600	600	600	600	600	600	600	600	600	600
52	610	610	610	610	610	610	610	610	610	610
53	620	620	620	620	620	620	620	620	620	620
54	630	630	630	630	630	630	630	630	630	630
55	640	640	640	640	640	640	640	640	640	640
56	650	650	650	650	650	650	650	650	650	650
57	660	660	660	660	660	660	660	660	660	660
58	670	670	670	670	670	670	670	670	670	670
59	680	680	680	680	680	680	680	680	680	680
60	690	690	690	690	690	690	690	690	690	690
61	700	700	700	700	700	700	700	700	700	700
62	710	710	710	710	710	710	710	710	710	710
63	720	720	720	720	720	720	720	720	720	720
64	730	730	730	730	730	730	730	730	730	730
65	740	740	740	740	740	740	740	740	740	740
66	750	750	750	750	750	750	750	750	750	750
67	760	760	760	760	760	760	760	760	760	760
68	770	770	770	770	770	770	770	770	770	770
69	780	780	780	780	780	780	780	780	780	780
70	790	790	790	790	790	790	790	790	790	790
71	800	800	800	800	800	800	800	800	800	800
72	810	810	810	810	810	810	810	810	810	810
73	820	820	820	820	820	820	820	820	820	820
74	830	830	830	830	830	830	830	830	830	830
75	840	840	840	840	840	840	840	840	840	840
76	850	850	850	850	850	850	850	850	850	850
77	860	860	860	860	860	860	860	860	860	860
78	870	870	870	870	870	870	870	870	870	870
79	880	880	880	880	880	880	880	880	880	880
80	890	890	890	890	890	890	890	890	890	890
81	900	900	900	900	900	900	900	900	900	900
82	910	910	910	910	910	910	910	910	910	910
83	920	920	920	920	920	920	920	920	920	920
84	930	930	930	930	930	930	930	930	930	930
85	940	940	940	940	940	940	940	940	940	940
86	950	950	950	950	950	950	950	950	950	950
87	960	960	960	960	960	960	960	960	960	960
88	970	970	970	970	970	970	970	970	970	970
89	980	980	980	980	980	980	980	980	980	980
90	990	990	990	990	990	990	990	990	990	990
91	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000



# Cost Estimates

Methods



- Four different methods
  - RSMeans SQFE-Estimator
  - German SQFE-Estimator
  - Own Calculations with RSMeans as base
  - Reference Project

A

E


C

L

S

# Cost Estimates

SQFE Parameters



## RSM Means SQFE

*(Based on basic constructions)*

- Building Type
- Story Count
- Story Height
- Floor Area
- Perimeter

## German SQFE

*(Based on 13 universities with advanced laboratory facilities)*

- Site Total
- Gross Floor Space
- Outside Area
- Excavation
- Footprint
- Exterior Walls
- Interior Walls
- Ceiling
- Roof

A


E

C

L

S

# Cost Estimates Reference Project



- Project Name:  
Arrheniuslaboratoriet
- Building Type: School Building
- Location: Stockholm, Sweden
- Floor Area: 27 000 SF
- Cost: \$6 150 000
- Cost/SF: \$228
- Similar Building Program



A

E


C

L

S





# Cost Estimates Result Data



## Transparency

## ReUse

	Concrete	Steel	Concrete	Steel
RSMMeans SQFE	\$5 647 000 (\$179/SF)	\$5 835 500 (\$185/SF)	\$5 764 500 (\$173/SF)	\$5 992 000 (\$180/SF)
German SQFE	\$7 361 000 (\$233/SF)	\$7 361 000 (\$233/SF)	\$7 660 000 (\$230/SF)	\$7 660 000 (\$230/SF)
Reference Project w. factor	\$6 866 000 (\$217/SF)	\$6 866 000 (\$217/SF)	\$7 437 500 (\$223/SF)	\$7 437 500 (\$223/SF)



A


E

C

L

S

# Cost Estimates Calculations



## Transparency

## ReUse

Concrete

Steel

Concrete

Steel

Own Calcs.

\$6 767 000

\$6 930 000

\$6 677 000


\$6 858 000

(\$214/SF)

(\$219/SF)

(\$200/SF)

(\$206/SF)



■ Substructure

■ Shell

■ Interiors

■ Services

■ Sitework

■ Indirect Costs

A

E



C

L

S

# Cost Estimates


Inflation Data



A  
E  
C  
L  
S

# Cost Estimates

Inflation Forecast




A

E


C

L

S



# Construction Methods



- Cast-in-place concrete (prefab auditorium roof)
- Similar beam sizes
- No building components greater than 50'
- Just in time delivery

A


E

C

L

S

# Risk Items



A

E

C

L

S

Period	Risk Category	Risk name	Risk Allocation		Responsible
			Contractor	Owner	
Construction Period	political risks	changes of principles (DIN, Euro code)	x		all
		permission problems	x	x	owner
		party political changes	x	x	owner
		restrictions on import/export		x	owner
	commercial risks	increasing prices of resources	x		CM, LCFM
	legal risks	changes in law		x	owner
		building license		x	owner
		change of sales tax		x	owner
		purchase of sight		x	owner
	force majeure	war		x	all
		storm	x	x	all
		<b>flooding risk</b>	<b>x</b>		<b>all</b>
	planning risks	wrong sizing	x		A, E
		structural risk	x		E
	construction risks	divergence of masses	x		
		exceeding construction schedule	x		CM
		defective material	x		
		time lag project start	x		
		accessibility building site	x		
		resident risk	x		
		fire risk	x		
		financing risks	changes of interests	x	
		inflation risk		x	
	illiquidity of customer	x			
	depression	x			
personnel risks	illness/accidents	x		CM	
	mistakes from workers	x		CM, LCFM	
	loss of workers	x		CM	
	liability in case of damage	x		CM, LCFM	
	strike	x		CM, LCFM	
Operation Period	political risks	changes of principles (DIN, Euro code)	x		all
	legal risks	changes in law		x	owner
		change of sales tax		x	owner
	operation risks	operation efficiency			

# Flooding Strategy

Idea	Doable?
Lifting the building up	No
Reduced damages	Yes
Aqua Barrier	No
Manual flood barrier	No
Automatic flood barrier	No
Building a dam	No
Impermeable bowl	Yes



Strategy for  
„Transparent“



Strategy for  
„ReUse“

A


E

C

L

S

# Flooding Strategy



“Let it in”

## Reduced damages

Arrangement of rooms and facilities

easy to clean

Action plan for tenant

Present value of future payments: **\$25,000**

“Keep it out”

## Impermeable bowl

Bowl of water impermeable concrete

Windows above flood level

No doors in first floor

Present value of future payments: **\$15,000**

A

E

C


L

S




# Flooding Integration


Architect:  
Placing windows



Construction  
Managers:  
Site layout



LCFM:  
Repair costs



A

E

C

L


S

# Sustainability

Focus on water reuse and geothermal energy

No focus on photovoltaic

Precipitation



Soil conditions



A

E

C

L

S


# Geothermal

Excellent site conditions for geothermal system, heat transfer in moist soil

Geothermal cages around pile foundation

Minimal ground disturbance

no extra boreholes







## Combination underfloor and ceiling air distribution

LEVEL 3: Underfloor Distribution

LEVEL 2: Underfloor distribution

LEVEL 1: Ceiling Distribution






Radiant heating: tubing embedded in concrete slab will be safe from flooding


Minimal mechanical ventilation in offices and classrooms

Underfloor distribution for auditorium



# Water Reuse

Pretreatment system for greywater  
Rainwater directly to storage tank



A

E

C

L

S

# LEED



- Minimal site disturbance and filters for runoff during construction
- Reuse of existing building materials for façade and interior
- Efficient HVAC systems and heat recovery
- Graywater reuse/rainwater harvesting
- On site renewables: geothermal
- Maximum daylight and natural ventilation strategies
- Maximum occupant comfort and safety:
  - Low VOC materials, occupant control of windows and task lighting,
- Measurement and verification strategies
  - Flexible systems like underfloor allow for reconfiguration according to performance evaluations

A


E

C

L

S

# Building Program



A

E

C

L

S



# Life Cycle Benchmarks

Ratio	Transparency	Reuse	Goal
non assignable area / assignable area	0,421	0,403	minimize
circulation area / usable area	0,244	0,229	minimize
building surface / building volume	0,099	0,093	minimize

A

E


C

L

S

# River Team

Communication, Collaboration, Cooperation




# Communication Wave

1200 messages in 64 Waves

Mainly discipline Waves

Gadgets to expand functional range


Planning Gadget



Mind Map Gadget




Napkin Gadget




# Collaboration Eliminating creativity

'''



# Cooperation Integration



# Decision Matrix

Rating: 1 low - 5 high

	TRANSPARENCY		REUSE	
aspect	concrete	steel	concrete	steel
Program fulfill	4	4	2	2
Response to the context	3	3	5	5
Big idea	2	2	4	4
Innovation	3	3	4	4
Floor to ceiling height	4	2	3	5
Cantiliver support	2	4	3	5
Lateral System	4	2	5	3
Connections	3	5	3	4
Construction costs	3	1	4	2
Constructability	2	4	3	5
Construction schedule	4	5	4	5
Prefabrication	1	4	2	5
Flexibility of spaces	4	5	3	2
Space efficiency	3	3	4	4
Flood prevention	2	2	4	4
Sustainability	2	2	4	4
Future design potentials	3	3	5	5
<b>sum</b>	<b>49</b>	<b>54</b>	<b>62</b>	<b>68</b>

A  
E  
C  
L  
S

# *River Team Presents*

ReUse



A

E

C

L

S

