



María[A]
Puerto Rico



Chris [SE]
Stanford



Wenhao [SE]
Stanford



Rob [MEP]
Stanford



Gustav [CM]
Sweden



Sabrina[LCFM]
Germany

ISLAND TEAM

*“No man is an island, entire of itself;
every man is a...part of the main...”*
-John Donne

Final Presentation

Rob Best, Maria Carrion, Wenhao Chen, Chris Lee, Sabrina Lingemann, Gustav Westphal


Puerto Rico

2



University of Puerto Rico

3




Island Team 05-11-2012

Site constraints


4

- Earthquakes: seismically active area due to close fault
- Hurricanes: frequent storms during summer and fall

**Total Storm Days by Week for PR
Within 200 Miles
(1900 - 2011)**



**Total Storms Affecting PR by Decade
Within 200 Miles
(1900 - 2011)**



Source: <http://www.nc-climate.ncsu.edu/climate/hurricanes/statistics>

Climate conditions

5

- Climatic Design Conditions
 - 2% Cooling Design Temperature: 89.2 F
 - 99% Heating Design Temperature: 70.8 F
 - No Heating Required

- Average Relative Humidity: 76.5%

- Yearly Rainfall: 56.43 inches
 - Monthly Range: 1.95 inches to 6.35 inches


Perception of Climate

6



The Boomerang

7



Concept Decision


8

	Average Weighting	Boomerang Steel	Boomerang Concrete	Floating Box Steel	Floating Box Concrete
Time targets	15,10 %	2,746	3,691	3,091	3,880
Cost targets	27,45 %	2,794	3,732	3,267	3,804
Quality targets	57,45 %	3,742	3,986	3,313	3,535
Total	100 %	3,307	3,879	3,288	3,732

Boomerang



Floating Box




maximum score: 5

Target Value Design

9

Targets developed with our owners:

- Spatial requirements
- Social & educating building
- LEED + DGNB sustainability
- Energy performance >25% below baseline
- Integration into environment
- Integrated biomimicry concepts
- Structural performance in hurricanes
- Flexibility of the building



- Completion earlier
- Labs ready earlier
- Quick build up after hurricane

- < 880,000 \$ annual rent
- Risk surcharge for hurricanes included
- Space efficiency and simplicity for o+m

SWOT of Boomerang Concrete


10

	Helpful	Harmful
Internal origin	Strengths <ul style="list-style-type: none">• Social building• Integrated into environment• Adapted to weather conditions• Local production• Low construction costs	Weaknesses <ul style="list-style-type: none">• Rather high o&m costs (energy, cleaning, etc.)• Rather low flexibility
External origin	Opportunities <ul style="list-style-type: none">• Good opportunities to improve sustainability• Natural ventilation• Educating building (e.g. biomimicry and sustainability)	Threats <ul style="list-style-type: none">• Hurricanes and heavy rain endanger construction and operation• Rather low sustainability over lifetime

POP Challenge


11

- **P**roduct – aspects of the building
- **O**rganization – who is proactive/reactive?
- **P**rocess – team process




Biomimicry Challenge

12



Biomimicry Challenge

13



Architectural Inspiration

14



- Comfortable space in tropical climate.
- Provides Natural illumination
- Maximizes Natural Ventilation
- Provides a sense of security and visual comfort.

Biomimicry Inspiration

15



- ❑ Tropical American plants with a deeply cleft calyx.
- ❑ They are common in Puerto Rico
- ❑ Chosen for their ability to collect water in the central core and in between leaves; this provides a source of water for other organisms.
- ❑ In the case of the Bird of Paradise, its leaves move according to humidity levels and temperature.

Structural Ideas

16



- How do we prepare for Mother Nature?
- Use of developing technology
 - Shear Splices
 - Rocking Frames
 - Shear Walls

MEP Ideas


17



- Biomimicry: natural cooling and ventilation
- Adaptive comfort suitable for Puerto Rico
- Building management with some individual control
 - Enhanced social space
 - Resilient against future use and climate changes


Natural Ventilation Potential

18




Site Plan

19




Architectural Floorplan 1



20

- Emergency Stairs
- Restrooms
- Auditorium
- Mechanical Room
- Café




Structural Floorplan 1




21


Columns	Member Size
Exterior	24" x 24"
Interior	14" x 14"




MEP Floorplan 1



-  Supply Duct
-  Return Duct




Architectural Floorplan 2




23

- Emergency Stairs
- Large Classrooms
- Small Classrooms
- Tech. Office
- Restrooms
- Mechanical Room
- Instructional Labs




Structural Floorplan 2




24

Columns	Member Size
Exterior	24" x 24"
Interior	14" x 14"
Cantilever	20" x 20"

Beams	18" x 22"
-------	-----------




MEP Floorplan 2




25

-  Supply Duct
-  Return Duct




Architectural Floorplan 3




26

- Emergency Stairs
- Restrooms
- Mechanical Room
- Instructional Labs
- Seminar Rooms
- Faculty Offices
- Administration




Structural Floorplan 3




27

Columns	Member Size
Exterior	24" x 24"
Interior	14" x 14"
Cantilever	20" x 20"


Beams	18" x 22"
-------	-----------




MEP Floorplan 3



- Supply Duct
- Return Duct



Section A-A



29



Section B-B




30



Evolution of the Foundations

31



Eliminated due to overturning moment.




Spread Footings

Evolution of the Foundations

32

- Accounts for the tension force
- Interferes with the underground water tank used for water recycling.



Eliminated due to
water tank placement


Pile Footings

Evolution of the Foundations

33

- Shallow foundation
- Accommodates the water tank
- Time and cost is comparable to pile foundation

100' by 100'
30" thickness





Mat Foundation

Evolution of Roof

34


Post-Tensioned
Waffle Slab
Depth: 20 inches

**3'-0" MODULE
(30" x 30" Dome System)**



Old and New Roof

35




Architectural Model 3D

36




Architectural Model 3D

37




Structural Model 3D

38




MEP Model 3D


39



Challenges



Floor Sandwich / Ventilation



Wind Availability

42

- Sea breezes from east across site
 - ▣ Naturally cooler than stagnant air
 - ▣ Westward side receives some wind exposure


- Average wind speed: 700 fpm
 - ▣ Typically varies between 150 and 1600 fpm

- Wind speed highest in afternoon when hottest

Wind Speeds

43

□ Wind Speeds (fpm)




Natural Ventilation Strategy

44


- Size for no more than 3F rise across room
 - 300 fpm in most spaces
 - Achievable most hours of year
- Maximum 700 fpm for ventilation in rooms
 - Achievable many hours of year
 - Less than 1 F rise
- Strategies:
 - Operable windows and grilles on both sides of room of at least 5% of floor area
 - Interior return fans to draw air inward

Review with Mentors



Natural Ventilation

46




Strategy to Achieve Net Zero

47

1. Baseline building according to IMC
2. Window shading and efficient fans
3. Setpoint to upper limit of ASHRAE standard
4. Improved insulation and windows
5. Photosensors for daylighting
6. Switch to adaptive comfort with natural ventilation

Energy Saving Strategies

Energy Use (kWh)



eQuest Results

49

- 146,610 kWh on-site energy per year
 - Design temperature of 83F (limit of acceptability with adaptive comfort standard)
 - 184,400 kWh at design temp. of 76F (ASHRAE)

- 44 tons maximum cooling load
 - Occurs on October 19, 4 pm
 - Reduced from 60 tons with change in setpoint

- 49% percent reduction from baseline

PV Panels


50

- Polycrystalline silicon PV panels
- Most common, less expensive
- Not tilted to be more resistant during hurricanes
- Energy gained:
194,293 kWh/year
- Energy needed:
184,840 kWh/year
- Investment costs: \$ 92,600




Trade-off PV Panels

51



Dynamic Façade

52




Façade Override

53



Enclosed Façade

54



Façade Material

55



- corten steel
 - high strength
 - weather resistance
 - strong enough to protect windows
 - nice appearance




Strengths & Weaknesses Façade

56

	Strengths	Weaknesses
Quantitative	<ul style="list-style-type: none">• Saves energy costs• Smaller HVAC system possible• Protects glass windows in hurricanes• Lower cleaning costs for windows	<ul style="list-style-type: none">• Construction costs• Operation costs• Maintenance and regular replacement costs for motors• Hurricane risk buffer
Qualitative	<ul style="list-style-type: none">• Aesthetical beauty• Perfect shading• Advances natural ventilation• Local / biomimicry solution• Material perfect for humid and rainy climate	<ul style="list-style-type: none">• Motors and sensors quite sensitive

Façade Financing Possibility


57



Trade-off Façade


58

Profitable after 5 years



Rainwater Harvesting

59




10,000 gallon tank fed by permeable PVC pipe



Rainwater Harvesting

60

- Can harvest 80,000 gallons/year
- Non-potable use: 73,800 gallons/year
- Conclusion: rainwater harvesting beneficial




Trade-off rainwater harvesting


61

- Rainwater gained: 80,000 gal/year
- Non-potable water needed: 73,800 gal/year
- Potable water needed in addition: 66,960 gal/year
- Investment costs: \$ 4,150

Profitable after 7 years




Development Organization & Process



Structural Analysis Process

63



Hand Calculations


64

Back of Envelope Calculation

- Used for initial and major changes in the product

What is a reasonable size to get the process to start with?


What sizes should the team expect to allow them to move forward with their processes?



Revit Structure 2010

65

- Integration with Architecture and MEP
- Used for clash detections
- Enables visual communication on the product





ETABS/ADAPT

67

- Structural Analysis Modeling Program
- Used to analyze:
 - Gravity Loading
 - IBC 2009 Design Combination
 - Post tensioned Concrete Tendons
 - Lateral Loading

What does the software tell us?




Hand Calculation

68

Spot Checking

- Validates the process
- Ensures that the whole “Garbage In, Garbage Out” syndrome did not happen.




Does that make sense?

Did the software provide us with meaningful results?


Gravity Load Path

69



Gravity Load Path


70



ETABS Analysis

71

- ETABS Animation!



ETABS Data


72

Input Loading Data

Load Type	Floor	Values
Dead Load	Typical Floor	120 psf
	Roof	80psf
Live Load	Typical Floor	60 psf
	Roof	30psf
Wind Load	Typical Floor	43 kips
	Roof	25 kips
Seismic	Base Shear	765 kips

Data Result


	Maximum Beam Deflection	1.27 in
	Axial Force @ Column C31	254 kips
	Shear Force @ Column C31	330 kips



ADAPT Analysis


73

Max Deflection: 1.18"




Tendon Height Diagram

File: Support Line 49_pt




ADAPT Analysis

74



Lateral Resistance

75



12" Shear Wall

Lateral Resistance


76

Criteria	Value
Site Condition	D
Ss	0.9
S1	0.31

Floor	Applied Load
Roof	192 k
3 rd	383 k
2 nd	192 k
Base	764 k


Lateral Load Path

77



Lateral Analysis Results


78



Dominate
Period:
0.358s

Lateral Analysis Results

79




Cd	4
Max Elastic Defl.	0.32"
Code Amplified IDR	1.1%
Code Limit IDR	2%

Lateral Analysis Results




80

- ETABS Animation!



Shear Wall Design

81



**Foundation's Reinforcement
are not shown**

Shear Wall design


82

Type	Reinforcement
Vertical: within 30" from the edge	#11 Bars @ 4"
Vertical: Others	#11 Bars @12"
Shear Reinforcement	# 6 Bars @8"

Earthquake Recovery

83

Applied Technology Council ATC-13 (1985)



Result:

Probability of MMI 7 : ~ 2.3%



Damage State Level 4

10-80 Days for Repair

Hurricane Risk Surcharge

84

- Calculating the risk surcharge for hurricanes and natural catastrophes:
 - construction period
 - operation period



Risk Assessment Results

85

severity of consequences ↑


<ul style="list-style-type: none"> • complaints • finance • owner bankruptcy 	<ul style="list-style-type: none"> • material prices • income • interface • inflation 	<ul style="list-style-type: none"> • natural catastrophes during operation
<ul style="list-style-type: none"> • contract • input • vandalism • maintenance 	<ul style="list-style-type: none"> • planning • demand • resource prices • performance change • technology • management • change of guidelines • interest rate 	<ul style="list-style-type: none"> • weather conditions during construction
<ul style="list-style-type: none"> • ground / soil • technical construction • operation 	<ul style="list-style-type: none"> • tendering 	

probability of occurrence →


- Risk surcharges:
 - ▣ construction period: \$ 250,000
 - ▣ operation period: \$ 875,000

BIM Coordination

86




BIM Coordination




BIM Coordination

88

Clash detection 2012-04-12				
	Resolved			
	Active			
	Accepted			
	In progress/partly resolved			
Clash	Status	Detected on date	Comment/action	Picture
Missplaced columns in facade	Resolved	2012-04-12	Correct placemet in atrium	
	In progress/partly resolved	2012-04-16	Atrium columns still wrong Move architecture	
Missplaced columns interior	Active	2012-04-12	Hide inside w alls? Some clash with open space	
Facede wall to thin	Resolved	2012-04-12	Make facede thicker?	


Site Logistics

89




Site Logistics

90



Site Logistics

91



Truck Route

92




One way traffic

Off Site Logistics

93

- Concrete: 4.6 mi (map)
- Precast concrete: 8.7 mi
- Glazing: 7.0 mi
- Hospital: 0.7 mi
- Equipment rental: 6.3 mi
- Off site storage: 6.1 mi



Equipment

94

- Excavator with high capacity
- Weight: 72 500 lb



- Small excavator for sewer etc.
- Weight: 7 800 lb



Equipment


96

- Sky lift for fitting of windows and shading
- Used for material laydown



Schedule

97



9-14-2015
Construction start


2-4-2016
Lab finished

4-19-2016
Building enclosed

8-1-2016
Construction finished
4 weeks early

Alternative Schedule

98




2016-02-04
Lab finished

2016-05-02
Lab finished

Constructability 4D

99



Construction innovations

100

- Tablets with 3D model of the building
→ *better understanding of the building*
- Over night material laydown
→ *reduces construction time*




Cost Estimate

101

Construction cost




Cost per SF




Cost Estimate

102




Cost Estimate

103




Life Cycle Costs

Life Cycle Costs (NPV)




Sensitivity analysis of LCC



LCC Comparisons


Necessary rent payments to cover LCC (base rate)




Property Cash Flow

106

Break-even in year 11




Real Cash Flows




Loan structures & financial ratios

108



Sustainability Approach

109



208 PV panels

Water Harvesting
80,000 Gal./Yr.

Balconies for social
sustainability

Re-Use of Excavated
Terrain

Dynamic Facade

LEED Gold



110

Category	Max. Points	Points given
Sustainable site	26	15
Water Efficiency	10	9
Energy and Atmosphere	35	35
Materials and Resources	14	4
Indoor Environmental Quality	15	14
	100	77

Certified 40 to 49 points

Silver 50 to 59 points

Gold 60 to 79 points

Platinum 80 to 110

DGNB Silver

111

Evaluation Area	Criteria Group	Average Performance	Total Performance
Environmental Quality	Life Cycle Analysis	87,5 %	77,4 %
	Global and Local environmental Impact		
	Ressource Consumption and Waste Generation		
Economic Quality	Life Cycle Costs	70,0 %	
	Economic Performance		
Sociocultural and Functional Quality	Health, Comfort and User Friendliness	74,8 %	
	Functionality		
	Aesthetic Quality		
Technical Quality	Technical Quality of Building Design and Systems	75,0 %	
Process Quality	Quality of the Planning Process	82,4 %	
	Construction Quality		
Site Quality	Site Quality	(not counted)	


Bronze > 50 %

Silver > 65 %

Gold > 80 %

Target Value Design

112



Team communication



113

- Informal communication
- Exchange of links and videos
- “In-between” communication

- Smaller chats
- Sub-group meetings
- Back-up to GoToMeeting


- Team meetings
- Sub-group meetings

- Results
- Forums in box for discussions




Team Development

114




Team Development

115



Team Process Assessment Survey

Team Communication Pace



Gus EXHAUSTED	CONFUSED	ECSTATIC	GUILTY	SUSPICIOUS
ANGRY	HYSTERICAL	FRUSTRATED	SAD	Chri CONFIDENT
EMBARRASSED	HAPPY	MISCHIEVOUS	DISGUSTED	FRIGHTENED
ENRAGED	ASHAMED	CAUTIOUS	SMUG	DEPRESSED
Rob OVERWHELMED	Sabr HOPEFUL	LOVELY	LOVESTRUCK	JEALOUS
BORED	SURPRISED	Mar ANXIOUS	SHOCKED	SHY

Team Culture

117



Team Culture



Thank you!

Humberto Cavallin

Mayra Jimenez

David Bendet

Willem Kymmell

Greg Luth

Nick Arenson

Erik Kneer

Greg Deierlein

Eduardo Miranda

Anirudh Rao

Florian Aalami (ADAPT)

Renate Fruchter

Derek Ouyang

Riam Firouz

Michael Seaman

Afaan Naqvi

Kyle Adams

John Nelson

Erik Kolderup

Peter Rumsey

Kjell Nilver

Fredrik Wincent (Veidekke)

Nima Assadi (Veidekke)

Stefan Söderberg (Veidekke)

Björn Wündsich

Matthias Ehrlich

Rubén (Palisade @Risk)

Steve Beeusaert (Palisade @Risk)

Jaime Weisberg (Palisade @Risk)