CS106A Handout #24S Winter 2015 March 2, 2015

## **Section Solutions 8**

```
import acm.program.*;
import acm.util.*;
import java.util.*;
import java.io.*;
public class FlightPlanner extends ConsoleProgram {
  /* The name of the flights file. */
 private static final String FLIGHTS_FILE = "flights.txt";
  /* The separator used to delimit the start and end of a flight. */
 private static final String FLIGHT DELIMITER = " -> ";
  /* A map from the lower-case representation of a name to its original
  * capitalization.
  private HashMap<String, String> capitalizationMap
   = new HashMap<String, String>();
  /* A map from cities to cities reachable from there. The keys in the
  * map are the lower-case representations of the city names, and the
  * values are the lowercase representations.
  private HashMap<String, ArrayList<String>> flights
   = new HashMap<String, ArrayList<String>>();
  public void run() {
   /* Populate the data structures. */
   loadFlights();
   /* Find the flight path. */
   ArrayList<String> flightPath = chooseFlightPath();
   /* Display the flight path. */
   printFlightPath(flightPath);
  }
```

```
/**
* Populates the internal data structures using the flight information from the
* file.
*/
private void loadFlights() {
 try {
   BufferedReader br = new BufferedReader(new FileReader(FLIGHTS FILE));
   while (true) {
      String line = br.readLine();
     if (line == null) break;
     /* If the line is nonempty, process it as a flight entry. */
     if (!line.isEmpty()) {
       processFlight(line);
 } catch (IOException e) {
   throw new ErrorException(e);
}
* Given a line of the file encoding a flight, extracts the flight information
* from that line.
 * @param line The line to parse.
private void processFlight(String line) {
 /* Find where the -> in the string is, then get the source and
  * destination of the flight.
  */
  int splitPoint = line.indexOf(FLIGHT DELIMITER);
 String source = line.substring(0, splitPoint);
 String destination = line.substring(splitPoint + FLIGHT DELIMITER.length());
  /* If this is the first time we've seen the source, create an entry for it.
  * in our data structures.
  */
  if (!capitalizationMap.containsKey(source.toLowerCase())) {
   capitalizationMap.put(source.toLowerCase(), source);
    flights.put(source.toLowerCase(), new ArrayList<String>());
 }
 /* Add this flight. */
 flights.get(source.toLowerCase()).add(destination.toLowerCase());
}
```

```
/**
* Prompts the user to enter a flight path, returning the ultimate path. The
* returned path uses the lower-case representations of the city names.
 * @return The chosen flight path.
private ArrayList<String> chooseFlightPath() {
 ArrayList<String> result = new ArrayList<String>();
  /* Find out where we're starting. */
 String source = chooseStartingCity();
  result.add(source);
  /* Track which city we are currently at. */
 String currentCity = source;
 while (true) {
   String nextCity = chooseNextCity(currentCity);
    result.add(nextCity);
   /* Stop if we're back where we started. */
   if (source.equals(nextCity))
     return result;
    /* Update our position. */
   currentCity = nextCity;
 }
}
* Prompts the user to choose a starting city, returning the city that was
* chosen.
 * @return The city that was chosen.
private String chooseStartingCity() {
 displayWelcome();
 while (true) {
   String choice = readLine("Enter the starting city: ").toLowerCase();
   /* If this is a valid city, return it. */
   if (flights.containsKey(choice))
     return choice:
    /* Otherwise, reprompt. */
    println("Sorry, that's not a valid choice.");
 }
}
```

```
* Displays a nice welcome message to the user.
private void displayWelcome() {
  println("Welcome to Flight Planner!");
  println("Here's a list of all the cities in our database: ");
  /* List all the cities that we know of. One way to do this would be
  * to iterate across the capitalization map's keys and find the
  * associated values, but since we just want the properly-capitalized
  * cities we can just iterate over the value set.
  for (String city: capitalizationMap.values()) {
    println(" " + city);
}
/**
* Prompts the user to choose the next city in the path, which must be a city
* that's reachable from the current city.
 * @param currentCity The current city.
 * @return The next city in the path.
private String chooseNextCity(String currentCity) {
  printCitiesReachableFrom(currentCity);
  /* Get the properly-capitalized representation of the current city. */
  String printCity = capitalizationMap.get(currentCity);
  while (true) {
    String line =
     readLine("Where do you want to go from " + printCity + "? ").toLowerCase();
    /* If the city is reachable, go there. */
    if (flights.get(currentCity).contains(line)) {
     return line;
    println("Sorry, you can't go there from " + printCity +".");
 }
}
* Lists all the cities reachable from some given city.
 * @param city The city to list reachable cities from.
private void printCitiesReachableFrom(String city) {
  println("From " + capitalizationMap.get(city) + " you can go to: ");
  /* Iterate across the reachable cities. */
  for (String destination: flights.get(city)) {
    println(" " + capitalizationMap.get(destination));
 }
}
```

```
/**
 * Prints a human-readable representation of a flight path.
 *
 * @param path The flight path to display.
 */
private void printFlightPath(ArrayList<String> path) {
    println("The route you've chosen is: ");

    /* Build up the path to display incrementally. */
    String toDisplay = "";
    for (int i = 0; i < path.size(); i++) {
        toDisplay += capitalizationMap.get(path.get(i));

        /* Insert an arrow in-between all of the cities. Be sure not to append
        * an unnecessary arrow at the end!
        */
        if (i != path.size() - 1)
            toDisplay += " -> ";
        }
        println(toDisplay);
    }
}
```