



The Internet

Chris Piech
CS106A, Stanford University

I came here to make friends
and program the internet...

... And I already made
friends.

For the second time ever in
CS106A:

Learning Goals

1. Write a program that can make internet requests
2. Write a program that can respond to internet requests



How does your phone
communicate with facebook?

The Java program on your
phone talks to the Java
program at **Facebook**

Face Book Server



* Android phones run Java. So do facebook servers



Face Book Server

Is this legit?




`piech@cs.stanford.edu`
is now logged in



Face Book Server

Send me the **full name** for
piech@cs.stanford.edu



"Chris Piech"



Face Book Server

Send me the **cover photo** for
piech@cs.stanford.edu



Face Book Server

Send the **profile photo** for
`piech@cs.stanford.edu`



Face Book Server

Send the **status** for
piech@cs.stanford.edu



"chillin"



Set the **status** for
piech@cs.stanford.edu
to be **"lecturing"**

Face Book Server




"success"



Send me the **status** for
piech@cs.stanford.edu

Face Book Server



"lecturing"



Background: The Internet



The internet is just many programs sending messages (as *Strings*)

Thanks Nick for the teaching YEAH



Background: The Internet



The internet is just many programs sending messages (as *Strings*)

Thanks Nick for the teaching YEAH




Background: The Internet



The internet is just many programs sending messages (as *Strings*)




Background: The Internet



The internet is just many programs sending messages (as *Strings*)



Background: The Internet



The internet is just many programs sending messages (as *Strings*)





There are two types of
internet programs. Servers
and Clients



Internet 101

Servers are computers (running code)

Face Book Server




=



Facebook's closest
datacenter is here

I am here






The Internet



Face Book Server





The Internet



Face Book Server




Get status for
`piech@cs.stanford.edu`



Piech, CS106A, Stanford University






The Internet




Face Book Server





The Internet



teaching

The Internet



Face Book Server






The Internet



Face Book Server




Piech, CS106A, Stanford University



teaching


The Internet

Face Book Server




Many computers can connect
to the same server

The Internet



Most of the Internet





There are two types of
internet programs. Servers
and Clients




First, the server

A Server's Simple Purpose

Request
`someRequest`

String
`serverResponse`



A Server's Simple Purpose

Request
someRequest

String
serverResponse

```
ChatServer
Starting server on port 8080...
getMsgs
newMsg
Added new message
getMsgs
Returned 1 messages
getMsgs
Returned 1 messages
newMsg
Added new message
getMsgs
Returned 1 messages
getMsgs
```



Servers on one slide

1

```
public String requestMade(Request request) {  
    // server code goes here  
}
```

2

```
// make a Server object  
private SimpleServer server  
    = new SimpleServer(this, 8000);
```

3

```
public void run() {  
    // start the server  
    server.start();  
}
```



A Server's Simple Purpose

1

```
public String requestMade(Request request) {  
    // server code goes here  
}
```

2

```
// make a Server object  
private SimpleServer server  
    = new SimpleServer(this, 8000);
```

3

```
public void run(){  
    // start the server  
    server.start();  
}
```



What is a Request?



```
/* Request has a command */  
String command;
```


```
/* Request has parameters */  
HashMap<String,String> params;
```

Request request

```
// methods that the server calls on requests  
request.getCommand();  
request.getParam(key); //returns associated value
```




Requests are like Remote Method Calls



Requests are like Remote Method Calls

Server





makeToast



getChocolate



Requests are like Remote Method Calls



makeToast



getChocolate

Requests are like Remote Method Calls



To make toast, I need a
parameter which is the
kind of bread




makeToast



Requests are like Remote Method Calls



I was given a parameter!



makeToast



Requests are like Remote Method Calls




`request.getParam("bread")`



`makeToast`




Requests are like Remote Method Calls



makeToast




Requests are like Remote Method Calls




makeToast



Requests are like Remote Method Calls




```
public String requestMade(Request request) {  
    String cmd = request.getCommand();  
    if(cmd.equals("makeToast")) {  
        Bread input = request.getParam("bread");  
        Bread output = runToaster(input);  
        return output.toString();  
    }  
    ...  
}
```



.toString()???




Requests are like Remote Method Calls




Requests are like Remote Method Calls



Requests are like Remote Method Calls




Requests are like Remote Method Calls



Requests are like Remote Method Calls



Requests are like Remote Method Calls



What is a Request?



```
/* Request has a command */  
String command;
```

```
/* Request has parameters */  
HashMap<String,String> params;
```

Request request

```
// methods that the server calls on requests  
request.getCommand();  
request.getParam(key); //returns associated value
```



A Server's Simple Purpose

1

```
public String requestMade(Request request) {  
    // server code goes here  
}
```

2

```
// make a Server object  
private SimpleServer server  
    = new SimpleServer(this, 8000);
```

3

```
public void run(){  
    // start the server  
    server.start();  
}
```



A Server's Simple Purpose

1

```
public String requestMade(Request request) {  
    // server code goes here  
}
```

2

```
// make a Server object  
private SimpleServer server  
    = new SimpleServer(this, 8000);
```

3

```
public void run(){  
    // start the server  
    server.start();  
}
```



What is a Port?



A Server's Simple Purpose

1

```
public String requestMade(Request request) {  
    // server code goes here  
}
```

2

```
// make a Server object  
private SimpleServer server  
    = new SimpleServer(this, 8000);
```

3

```
public void run(){  
    // start the server  
    server.start();  
}
```



Servers on one slide

1

```
public String requestMade(Request request) {  
    // server code goes here  
}
```

2

```
// make a Server object  
private SimpleServer server  
    = new SimpleServer(this, 8000);
```

3

```
public void run() {  
    // start the server  
    server.start();  
}
```



Echo Server



Echo Server

Request

Any Request

String

Length of the cmd



```
EchoServer
Starting server...
Request recieved hello
Request recieved this+is+a+test
Request recieved whatsGood
Request recieved ping
Request recieved ping
Request recieved ping
Request recieved pong
Request recieved ping
```






There are two types of
internet programs. Servers
and Clients



Then, the client

A Clients's Purpose



1. Interact with the user
2. Get data from its server
3. Save data to its server



Clients on one slide

```
try {  
    // 1. construct a new request  
    Request example = new Request("getStatus");  
  
    // 2. add parameters to the request  
    example.addParam("name", "chris");  
  
    // 3. send the request to a computer on the internet  
    String result = SimpleClient.makeRequest(HOST, example);  
} catch(IOException e) {  
    // The internet is a fast and wild world my friend  
}
```



Clients on one slide

```
try {  
    // 1. construct a new request  
    Request example = new Request("getStatus");  
  
    // 2. add parameters to the request  
    example.addParam("name", "chris");  
  
    // 3. send the request to a computer on the internet  
    String result = SimpleClient.makeRequest(HOST, example);  
} catch(IOException e) {  
    // The internet is a fast and wild world my friend  
}
```



Clients on one slide

```
try {  
    // 1. construct a new request  
    Request example = new Request("getStatus");  
  
    // 2. add parameters to the request  
    example.addParam("name", "chris");  
  
    // 3. send the request to a computer on the internet  
    String result = SimpleClient.makeRequest(HOST, example);  
} catch(IOException e) {  
    // The internet is a fast and wild world my friend  
}
```



Clients on one slide

```
try {  
    // 1. construct a new request  
    Request example = new Request("getStatus");  
  
    // 2. add parameters to the request  
    example.addParam("name", "chris");  
  
    // 3. send the request to a computer on the internet  
    String result = SimpleClient.makeRequest(HOST, example);  
} catch(IOException e) {  
    // The internet is a fast and wild world my friend  
}
```



Clients on one slide

```
try {  
    // 1. construct a new request  
    Request example = new Request("getStatus");  
  
    // 2. add parameters to the request  
    example.addParam("name", "chris");  
  
    // 3. send the request to a computer on the internet  
    String result = SimpleClient.makeRequest(HOST, example);  
} catch(IOException e) {  
    // The internet is a fast and wild world my friend  
}
```



Clients on one slide

```
try {  
    // 1. construct a new request  
    Request example = new Request("getStatus");  
  
    // 2. add parameters to the request  
    example.addParam("name", "chris");  
  
    // 3. send the request to a computer on the internet  
    String result = SimpleClient.makeRequest(HOST, example);  
} catch(IOException e) {  
    // The internet is a fast and wild world my friend  
}
```



Clients on one slide

```
try {  
    // 1. construct a new request  
    Request example = new Request("getStatus");  
  
    // 2. add parameters to the request  
    example.addParam("name", "chris");  
  
    // 3. send the request to a computer on the internet  
    String result = SimpleClient.makeRequest(HOST, example);  
} catch(IOException e) {  
    // The internet is a fast and wild world my friend  
}
```




Clients on one slide

```
try {  
    // 1. construct a new request  
    Request example = new Request("getStatus");  
  
    // 2. add parameters to the request  
    example.addParam("name", "chris");  
  
    // 3. send the request to a computer on the internet  
    String result = SimpleClient.makeRequest(HOST, example);  
} catch(IOException e) {  
    // The internet is a fast and wild world my friend  
}
```



Time for a little chat




Chat Server and Client





```
history = [
]
```



```
addMsg  
msg = Hello world
```





```
history = [  
    Hello world  
]
```



getMsgs
index = 0





```
history = [  
    Hello world  
]
```


[Hello world]





```
history = [  
    Hello world  
]
```


```
addMsg  
msg = Im here too
```





```
history = [  
    Hello world,  
    Im here too  
]
```



getMsgs
index = 1





```
history = [  
    Hello world,  
    Im here too  
]
```

[Im here too]



Chat Server

Chat Server



```
addMsg  
msg = text
```



```
getMsgs  
index = startIndex
```

