


CS 106A, Lecture 14

Events and Instance Variables

Reading:

Art & Science of Java, Ch. 10.1-10.4



HW4:
Breakout

The River of Java

Memory

Events

Animation

Graphics
Programs

You are here

Plan for Today

- Announcements
- Review: animation and null
- Event-driven programming
- Instance variables
- Whack-A-Mole
- Extra: Googly Eyes

Announcements

- BlueBook download available on the website
 - try it out with the second practice exam!
- Assignment 3 due tomorrow
- Assignment 4 out tomorrow
 - not due until the following Monday, but could be good exam practice for graphics + events

Plan for Today

- Announcements
- **Review: animation and null**
- Event-driven programming
- Instance variables
- Whack-A-Mole
- Extra: Googly Eyes

Animation

- A Graphics program can be made to animate with a loop such as:

```
public void run() {  
    // create shapes here  
    while (condition) {  
        update the position of shapes;  
        pause(milliseconds);  
    }  
  
}
```

- Animation effect: create frame, pause, move to next frame

Null

Null is a special variable value that objects can have that means “nothing”. Primitives cannot be null.

If a method returns an object, it can return **null** to signify “nothing”. (just say **return null;**)

```
// may be a GObject, or null if nothing at (x, y)  
GObject maybeAnObject = getElementAt(x, y);
```

Objects have the value **null** before being initialized.

```
Scanner myScanner; // initially null
```

Null

Calling methods on an object that is **null** will crash your program!


```
// may be a GObject, or null if nothing at (x, y)
GObject maybeAnObject = getElementAt(x, y);
if (maybeAnObject != null) {
    int x = maybeAnObject.getX(); // OK
} else {
    int x = maybeAnObject.getX(); // CRASH!
}
```


Plan for Today

- Announcements
- Review: animation and null
- **Event-driven programming**
- Instance variables
- Whack-A-Mole
- Extra: Googly Eyes

Events

- **event:** Some external stimulus that your program can respond to.



- **event-driven programming:** A programming paradigm (common in graphical programs) where your code is executed in response to user events.

Events

- Program launches

Events

- Program launches
- Mouse motion
- Mouse clicking
- Keyboard keys pressed
- Device rotated
- Device moved
- GPS location changed
- and more...

Events

- Program launches
- Mouse motion
- Mouse clicking
- Keyboard keys pressed
- Device rotated
- Device moved
- GPS location changed
- and more...

Events

```
public void run() {  
    // Java runs this when program launches  
}
```

Events

```
public void run() {  
    // Java runs this when program launches  
}  
  
public void mouseClicked(MouseEvent event) {  
    // Java runs this when mouse is clicked  
}
```

Events

```
public void run() {  
    // Java runs this when program launches  
}  
  
public void mouseClicked(MouseEvent event) {  
    // Java runs this when mouse is clicked  
}  
  
public void mouseMoved(MouseEvent event) {  
    // Java runs this when mouse is moved  
}
```


Example: ClickForDaisy

```
import acm.program.*;
import acm.graphics.*;
import java.awt.*;
import java.awt.event.*;           // NEW

public class ClickForDaisy extends GraphicsProgram {


    // Add a Daisy image at 50, 50 on mouse click
    public void mouseClicked(MouseEvent event) {
        GImage daisy = new GImage("res/daisy.png", 50, 50);
        add(daisy);
    }
}
```

MouseEvent Objects

- A MouseEvent contains information about the event that just occurred:

Method	Description
<code>e.getX()</code>	the x-coordinate of mouse cursor in the window
<code>e.getY()</code>	the y-coordinate of mouse cursor in the window

Example: ClickForDaisies



Example: ClickForDaisies

```
public class ClickForDaisies extends GraphicsProgram {  
  
    // Add a Daisy image where the user clicks  
    public void mouseClicked(MouseEvent event) {  
        // Get information about the event  
        double mouseX = event.getX();  
        double mouseY = event.getY();  
  
        // Add Daisy at the mouse location  
        GImage daisy = new GImage("res/daisy.png", mouseX, mouseY);  
        add(daisy);  
    }  
}
```

Example: ClickForDaisies

```
public class ClickForDaisies extends GraphicsProgram {  
  
    // Add a Daisy image where the user clicks  
    public void mouseClicked(MouseEvent event) {  
        // Get information about the event  
        double mouseX = event.getX();  
        double mouseY = event.getY();  
  
        // Add Daisy at the mouse location  
        GImage daisy = new GImage("res/daisy.png", mouseX, mouseY);  
        add(daisy);  
    }  
}
```

Types of Mouse Events


- There are many different types of mouse events.

– Each takes the form:

```
public void eventName(MouseEvent event) { ...
```

Method	Description
mouseMoved	mouse cursor moves
mouseDragged	mouse cursor moves while button is held down
mousePressed	mouse button is pressed down
mouseReleased	mouse button is lifted up
mouseClicked	mouse button is pressed and then released
mouseEntered	mouse cursor enters your program's window
mouseExited	mouse cursor leaves your program's window

Example: Doodler



Doodler

```
private static final int SIZE = 10;
```

```
...
```

```
public void mouseDragged(MouseEvent event) {  
    double mouseX = event.getX();  
    double mouseY = event.getY();  
    double rectX = mouseX - SIZE / 2.0;  
    double rectY = mouseY - SIZE / 2.0;  
    GRect rect = new GRect(rectX, rectY, SIZE, SIZE);  
    rect.setFilled(true);  
    add(rect);  
}
```


Doodler

```
public void mouseDragged(MouseEvent event) {  
    double mouseX = event.getX();  
    double mouseY = event.getY();  
    double rectX = mouseX - SIZE / 2.0;  
    double rectY = mouseY - SIZE / 2.0;  
    GRect rect = new GRect(rectX, rectY, SIZE, SIZE);  
    rect.setFill(true);  
    add(rect);  
}
```

Doodler

```
public void mouseDragged(MouseEvent event) {  
    double mouseX = event.getX();  
    double mouseY = event.getY();  
    double rectX = mouseX - SIZE / 2.0;  
    double rectY = mouseY - SIZE / 2.0;  
    GRect rect = new GRect(rectX, rectY, SIZE, SIZE);  
    rect.setFill(true);  
    add(rect);  
}
```

Doodler


```
public void mouseDragged(MouseEvent event) {  
    double mouseX = event.getX();  
    double mouseY = event.getY();  
    double rectX = mouseX - SIZE / 2.0;  
    double rectY = mouseY - SIZE / 2.0;  
    GRect rect = new GRect(rectX, rectY, SIZE, SIZE);  
    rect.setFilled(true);  
    add(rect);  
}
```

Doodler

```
public void mouseDragged(MouseEvent event) {  
    double mouseX = event.getX();  
    double mouseY = event.getY();  
    double rectX = mouseX - SIZE / 2.0;  
    double rectY = mouseY - SIZE / 2.0;  
    GRect rect = new GRect(rectX, rectY, SIZE, SIZE);  
    rect.setFilled(true);  
    add(rect);  
}
```

Review: animation and null: Events

- 1) User performs some action, like moving / clicking the mouse.
- 2) This causes an event to occur.
- 3) Java executes a particular method to handle that event.
- 4) The method's code updates the screen appearance in some way.



Revisiting Doodler

```
public void mouseDragged(MouseEvent event) {  
    double mouseX = event.getX();  
    double mouseY = event.getY();  
    double rectX = mouseX - SIZE / 2.0;  
    double rectY = mouseY - SIZE / 2.0;  
    GRect rect = new GRect(rectX, rectY, SIZE, SIZE);  
    rect.setFilled(true);  
    add(rect);  
}
```

What if we wanted the *same* GRect to track the mouse, instead of making a new one each time?

Plan for Today

- Announcements
- Review: animation and null
- Event-driven programming
- **Instance variables**
- Whack-A-Mole
- Extra: Googly Eyes


Instance Variables

```
private type name; // declared outside of any method
```

- **Instance variable:** A variable that lives outside of any method.
 - The *scope* of an instance variable is throughout an entire file (class).
 - Useful for data that must persist throughout the program, or that cannot be stored as local variables or parameters (event handlers).
 - *It is bad style to overuse instance variables*

DO NOT USE INSTANCE VARIABLES ON SNOWMAN!

Example: MouseTracker



Plan for Today

- Announcements
- Review: animation and null
- Event-driven programming
- Instance variables
- **Whack-A-Mole**
- Extra: Googly Eyes

Putting it all together



Whack-A-Mole


Let's use instance variables and events to make Whack-A-Mole!

- A mole should appear every half second at a random location, and stop once the user has gotten at least 10 points.
- If the user clicks a mole, remove it and increase their score by 1
- There should be a GLabel in the left corner showing their score



Exception

- If the user clicks an area with no mole, the program crashes.
 - A program crash in Java is called an **exception**.
 - When you get an exception, Eclipse shows red error text.
 - The error text shows the line number where the error occurred.
 - Why did this error happen?
 - How can we avoid this?





```
Problems @ Javadoc Declaration Console
WhackAMole [Java Application] /Library/Java/JavaVirtualMachines/jdk1.8.0_121.jdk/Contents/Home/bin/java (Apr 27, 2017, 10:46:49 PM)
Exception in thread "AWT-EventQueue-0" java.lang.NullPointerException
    at acm.graphics.GObjectList.remove(GContainer.java:187)
    at acm.graphics.GCanvas.remove(GCanvas.java:518)
    at acm.program.GraphicsProgram.remove(GraphicsProgram.java:215)
    at WhackAMole.mouseClicked(WhackAMole.java:52)
    at java.awt.AWTEventMulticaster.mouseClicked(AWTEventMulticaster.java:270)
    at java.awt.Component.processMouseEvent(Component.java:6536)
    at javax.swing.JComponent.processMouseEvent(JComponent.java:3324)
    at java.awt.Component.processEvent(Component.java:6298)
```

Plan for Today

- Announcements
- Review: animation and null
- Event-driven programming
- Instance variables
- Whack-A-Mole
- **Extra: Googly Eyes**

Extra Practice: GooglyEyes

Let's write a program called **GooglyEyes** that draws eyes whose pupils follow the user's mouse vertically as it moves around.



Plan for Today

- Announcements
- Review: animation and null
- Event-driven programming
- Instance variables
- Whack-A-Mole
- Extra: Googly Eyes

Next Time: Memory