




Animation

Chris Piech + Mehran Sahami
CS106A, Stanford University

Turing Award Winner Talks to CS106A



Pixar
Night

- **Turing Award** is like the nobel prize in CS
- Professor here at Stanford (CS107E, CS348)
- Founding employee at Pixar
- Wrote RenderMan, won 3 Academy Awards
- And just a really wonderful human.
- Thursday **May 7th, 4:30-6pm PDT** over Zoom, and attendance is restricted to students in CS 106A and CS 106B

<https://web.stanford.edu/class/cs106a/restricted/pixarnight>




Learning Goals

1. Feel more confident debugging
2. Write animated programs




You will be able to write Bouncing Ball



Great foundation



Move to Center



In our last episode...


Graphics from tkinter (aka tk)

```
import tkinter
```

```
# we write this for you, and include it  
# in all of your projects!  
def make_canvas(width, height, title):
```



Add square



Graphics from tkinter (aka tk)

```
import tkinter
```

```
# we write this for you, and include it  
# in all of your projects!  
def make_canvas(width, height, title):
```




```
def main():  
    canvas = make_canvas(CANVAS_WIDTH, CANVAS_HEIGHT, 'Move Square')  
    start_y = CANVAS_HEIGHT / 2 - SQUARE_SIZE / 2  
    end_y = start_y + SQUARE_SIZE  
    rect = canvas.create_rectangle(0, start_y, SQUARE_SIZE, end_y, fill='black')  
    canvas.mainloop()
```




```
def main():  
    canvas = make_canvas(CANVAS_WIDTH, CANVAS_HEIGHT, 'Move Square')  
    start_y = CANVAS_HEIGHT / 2 - SQUARE_SIZE / 2  
    end_y = start_y + SQUARE_SIZE  
    rect = canvas.create_rectangle(0, start_y, SQUARE_SIZE, end_y, fill='black')  
    canvas.mainloop()
```




```
def main():  
    canvas = make_canvas(CANVAS_WIDTH, CANVAS_HEIGHT, 'Move Square')  
    start_y = CANVAS_HEIGHT / 2 - SQUARE_SIZE / 2  
    end_y = start_y + SQUARE_SIZE  
    rect = canvas.create_rectangle(0, start_y, SQUARE_SIZE, end_y, fill='black')  
    canvas.mainloop()
```





```
def main():  
    canvas = make_canvas(CANVAS_WIDTH, CANVAS_HEIGHT, 'Move Square')  
    start_y = CANVAS_HEIGHT / 2 - SQUARE_SIZE / 2  
    end_y = start_y + SQUARE_SIZE  
    rect = canvas.create_rectangle(0, start_y, SQUARE_SIZE, end_y, fill='black')  
    canvas.mainloop()
```




```
def main():  
    canvas = make_canvas(CANVAS_WIDTH, CANVAS_HEIGHT, 'Move Square')  
    start_y = CANVAS_HEIGHT / 2 - SQUARE_SIZE / 2  
    end_y = start_y + SQUARE_SIZE  
    rect = canvas.create_rectangle(0, start_y, SQUARE_SIZE, end_y, fill='black')  
    canvas.mainloop()
```



```
def main():  
    canvas = make_canvas(CANVAS_WIDTH, CANVAS_HEIGHT, 'Move Square')  
    start_y = CANVAS_HEIGHT / 2 - SQUARE_SIZE / 2  
    end_y = start_y + SQUARE_SIZE  
    rect = canvas.create_rectangle(0, start_y, SQUARE_SIZE, end_y, fill='black')  
    canvas.mainloop()
```




```
def main():  
    canvas = make_canvas(CANVAS_WIDTH, CANVAS_HEIGHT, 'Move Square')  
    start_y = CANVAS_HEIGHT / 2 - SQUARE_SIZE / 2  
    end_y = start_y + SQUARE_SIZE  
    rect = canvas.create_rectangle(0, start_y, SQUARE_SIZE, end_y, fill='black')  
    canvas.mainloop()
```



Some “heavy
duty” variables
allow you to call
functions on them

```
def main():  
    canvas = make_canvas(CANVAS_WIDTH, CANVAS_HEIGHT, 'Move Square')  
    start_y = CANVAS_HEIGHT / 2 - SQUARE_SIZE / 2  
    end_y = start_y + SQUARE_SIZE  
    rect = canvas.create_rectangle(0, start_y, SQUARE_SIZE, end_y, fill='black')  
    canvas.mainloop()
```



You're now all graphics programmers!




Woot !

End review...

How do movies or games
animate?

Move to Center



* That's not quite toy story, but it is a start...



Animation Loop

```
def main():  
    # setup  
  
    while True:  
        # update world  
  
        # pause  
        time.sleep(DELAY)
```



Animation Loop

```
def main():  
    # setup  
  
    while True:  
        # update world  
  
        # pause  
        time.sleep(DELAY)
```

Make all the variables
you need.



Animation Loop

```
def main():  
    # setup  
    while True:  
        # update world  
  
        # pause  
        time.sleep(DELAY)
```


The animation loop is a repetition of heartbeats



Animation Loop

```
def main():  
    # setup  
  
    while True:  
        # update world  
        # pause  
        time.sleep(DELAY)
```

Each heart-beat, update
the world forward one
frame



Animation Loop


```
def main():  
    # setup  
  
    while True:  
        # update world  
        # pause  
        time.sleep(DELAY)
```

If you don't pause,
humans won't be able
to see it




Move To Center

```
def main():  
    # setup  
    canvas = make_canvas(CANVAS_WIDTH, CANVAS_HEIGHT)  
    r = canvas.create_rectangle(0, 0, 100, 100)  
    while not is_past_center(canvas, r):  
        # update world  
        canvas.move(r, 1, 0)  
        canvas.update()  
        # pause  
        time.sleep(DELAY)
```




We are ready...

Bouncing Ball




Milestone #1



Bouncing Ball

First heartbeat




Key variable: how much the ball position change each heartbeat?



Bouncing Ball

First heartbeat




The **move** function takes in
a change in x and a change in y




Bouncing Ball

Second heartbeat




Bouncing Ball

Third heartbeat




Bouncing Ball

What happens when we hit a wall?




Bouncing Ball

We have this velocity




Bouncing Ball

Our new velocity




Bouncing Ball

Seventh heartbeat




Bouncing Ball

Eighth heartbeat




Bouncing Ball

Ninth heartbeat




Bouncing Ball

We want this!




Bouncing Ball

This was our old velocity



Bouncing Ball

This is our new velocity




When reflecting horizontally: $\text{change_x} = -\text{change_x}$



Bouncing Ball


Tenth heartbeat



When reflecting horizontally: $\text{change_x} = -\text{change_x}$



Bouncing Ball



Hold up!


```
def make_ball(canvas):
```

If you get a copy when you pass a parameter. Does this copy the canvas??!!

*Large variables (objects) are stored using a reference which is like a **URL**. The URL gets copied when you pass the variable*



How do you share google docs?



https://docs.google.com/document/d/1eBtnEill3KHe_fFS-kSAOpXqeSXpbfTTMImOgj6I9dvk/



```
def main():
```

```
    canvas = make_canvas(...)
```

```
    make_ball(canvas)
```

```
def make_ball(canvas):
```

```
    canvas.create_rectangle( ... , fill='blue')
```

stack

heap

main



```
def main():
```

```
    canvas = make_canvas(...)
```



```
    make_ball(canvas)
```

```
def make_ball(canvas):
```


```
    canvas.create_rectangle( ... , fill='blue')
```

stack


heap




```
def main():  
    canvas = make_canvas(...)  
    make_ball(canvas)  
  
def make_ball(canvas):  
    canvas.create_oval( ... , fill='blue')
```




```
def main():  
    canvas = make_canvas(...)  
    make_ball(canvas)  
  
def make_ball(canvas):  
    canvas.create_oval( ... , fill='blue')
```



```
def main():  
    canvas = make_canvas(...)  
    make_ball(canvas)  
  
def make_ball(canvas):  
    canvas.create_oval( ... , fill='blue')
```





```
def main():  
    canvas = make_canvas(...)  
    make_ball(canvas)  
  
def make_ball(canvas):  
    canvas.create_oval( ... , fill='blue')
```



```
def main():  
    canvas = make_canvas(...)  
    make_ball(canvas)
```

```
def make_ball(canvas):  
    canvas.create_oval( ... , fill='blue')
```





```
def main():  
    canvas = make_canvas(...)  
    make_ball(canvas)  
  
def make_ball(canvas):  
    canvas.create_oval( ... , fill='blue')
```




stack

heap



```
def main():  
    canvas = make_canvas(...)  
    make_ball(canvas)  
  
def make_ball(canvas):  
    canvas.create_oval( ... , fill='blue')
```





Some variables are stored
with references

(which are like memory
URLs)



When passed as parameters

Variables that act like
their **value is copied**

Variables that act like
their **URL is copied**

boolean
integer
float
string

canvas
pixel
SimpleImage
list



Learning Goals

1. Feel more confident writing methods
2. Write animated programs



Special Graphics Functions

get the x location of the mouse

```
mouse_x = canvas.winfo_pointerx()
```

move shape to some new coordinates

```
canvas.moveto(shape, new_x, new_y)
```

move shape by a given change_x and change_y

```
canvas.move(shape, change_x, change_y)
```

get the coordinates of a shape

```
coord_list = canvas.coords(shape)
```

return a list of elements in a rectangle area

```
results = canvas.find_overlapping(x1, y1, x2, y2)
```

you can change a shapes color too

```
canvas.itemconfig(shape, fill=new_color, outline=...)
```

Come back on Monday to learn about lists!



