

Section #2: Random Variables

- 1. Warm-Up:** Express the probability mass function of the sum of two random integers between 1 and 4 (inclusive) as
1. a table;
 2. a graph;
 3. a mathematical function.

- 2. Breaking Vegas:** Consider any even money bet (e.g., bet “Red” in roulette) where there is $p = 18/38$ that you will win $\$Y$ and a $(1 - p)$ probability that you lose $\$Y$. Consider this algorithm for a series of bets:

1. Let $Y = \$1$.
2. Bet Y .
3. If you win, then stop.
4. If you lose, then set Y to be $2Y$ and goto step (2).

What are your expected winnings when you stop? It will help to recall that the sum of a geometric series $a^0 + a^1 + a^2 + \dots = \frac{1}{1-a}$ if $0 < a < 1$. Vegas breaks you: Why doesn't everyone do this?

- 3. Sending Bits to Space:** When sending binary data to satellites (or really over any noisy channel) the bits can be flipped with high probabilities. In 1947 Richard Hamming developed a system to more reliably send data. By using Error Correcting Hamming Codes, you can send a stream of 4 bits with 3 redundant bits. If zero or one of the seven bits are corrupted, using error correcting codes, a receiver can identify the original 4 bits.

Lets consider the case of sending a signal to a satellite where each bit is independently flipped with probability $p = 0.1$

- a. If you send 4 bits, what is the probability that the correct message was received (eg none of the bits are flipped).
 - b. If you send 4 bits, with 3 Hamming error correcting bits, what is the probability that a correctable message was received?
 - c. Instead of using Hamming codes, you decide to send 100 copies of each of the four bits. If for every single bit, more than 50 of the copies are not flipped, the signal will be correctable. What is the probability that a correctable message was received?
- 4. Launch:** Laura is a software engineer at the startup Acc.io, which has just launched its new website. This week she is “on call”: whenever something breaks, she gets a pager notification. She gets an average of one pager notification per 36 hours, independently and with the same frequency at all hours. What is the probability that Laura gets at least one notification between 1:00am and 7:00am? What is the standard deviation of the number of notifications?

5. **Missing Not at Random:** You collect data on whether or not people intend to vote for Ayesha, a candidate in an upcoming election. You send an electronic poll to 100 randomly chosen people. You assume all 100 responses are IID.

User Response	Count
Responded that they will vote for Ayesha	40
Responded that they will not vote for Ayesha	45
Did not respond	15

Let A be the event that a person says they will vote for Ayesha. Let M be the event that a user did not respond to the poll. We are interested in estimating $P(A)$, however that is hard given the 15 users who did not respond.

- What is the fraction of users that responded to the poll, $P(M^C)$?
- What is the probability that a user said they will vote for Ayesha, given that they responded to the poll $P(A|M^C)$?
- You estimate that $P(M|A) = \frac{1}{5}$ and that $P(M|A^C) = \frac{1}{10}$. What is $P(A|M)$? You may leave your answer in terms of $P(A)$. To make your future life easier, simplify your answer as much as possible.
- Using the same assumption as the previous part, calculate $P(A)$. You can make use of a function `root(a, b, c)` which returns the value of x such that $ax^2 + bx + c = 0$.