

Lecture 14: Imitation Learning in Large State Spaces¹

Emma Brunskill

CS234 Reinforcement Learning.

Winter 2022

¹With slides from Katerina Fragkiadaki and Pieter Abbeel

Refresh Your Understanding: Batch RL Policy Evaluation

• Select all that are true:

- ① Batch RL refers to when we have many agents acting in a batch f
- ② In batch RL we generally care more about sample efficiency than computational efficiency T
- ③ Importance sampling can be used to get an unbiased estimate of policy performance T
- ④ Q-learning can be used in batch RL and will generally provide a better estimate than importance sampling in Markov environments for any function approximator used for the Q F
- ⑤ Not sure

Refresh Your Understanding: Batch RL Policy Evaluation

- Select all that are true:
 - 1 Batch RL refers to when we have many agents acting in a batch
 - 2 In batch RL we generally care more about sample efficiency than computational efficiency
 - 3 Importance sampling can be used to get an unbiased estimate of policy performance
 - 4 Q-learning can be used in batch RL and will generally provide a better estimate than importance sampling in Markov environments for any function approximator used for the Q
 - 5 Not sure

Answer. F. T. T. F.

Class Structure

- Last time: Learning from offline data, overview and policy evaluation
- This time: Learning from offline data, policy evaluation and imitation learning
- Next time: Learning from offline data, policy optimization / learning

Today

- Importance sampling *contr*
- Imitation learning
 - Behavior cloning
 - Inverse RL

Importance Sampling is an Unbiased Estimator of True Expectation Under Desired Distribution If

$$\mathbb{E}_p[r] = \sum_x p(x)r(x) \quad \text{reweighting} \quad (1)$$

$$\approx \frac{1}{N} \sum_{i=1, x \sim q}^N \frac{p(x_i)}{q(x_i)} r(x_i) \quad (2)$$

- The sampling distribution $q(x) > 0$ for all x s.t. $p(x) > 0$ (Coverage / overlap)
- No hidden confounding

Check Your Understanding: Importance Sampling

We can use importance sampling to do batch bandit policy evaluation. Consider we have a dataset for pulls from 3 arms. Consider that arm 1 is a Bernoulli where with probability .98 we get 0 and with probability 0.02 we get 100. Arm 2 is a Bernoulli where with probability 0.55 the reward is 2 else the reward is 0. Arm 3 is a Bernoulli where with probability 0.5 it gets 1, else it gets 0. Select all that are true. T

- Data is sampled from π_1 where with probability 0.8 it pulls arm 3 else it pulls arm 2. The policy we wish to evaluate, π_2 , pulls arm 2 with probability 0.5 else it pulls arm 1. π_2 has higher true reward than π_1 .
- We cannot use π_1 to get an unbiased estimate of the average reward π_2 using importance sampling. T
- If rewards can be positive or negative, we can still get a lower bound on π_2 using data from π_1 using importance sampling F
but if $r \geq 0$ true
- Now assume π_1 selects arm1 with probability 0.2 and arm2 with probability 0.8. We can use importance sampling to get an unbiased estimate of π_2 using data from π_1 . T
- Still with the same π_1 , it is likely with $N=20$ pulls that the estimate using IS for π_2 will be higher than the empirical value of π_1 . F
VAI 2017 Drouot
- Not Sure

Check Your Understanding: Importance Sampling

We can use importance sampling to do batch bandit policy evaluation. Consider we have a dataset for pulls from 3 arms. Consider that arm 1 is a Bernoulli where with probability .98 we get 0 and with probability 0.02 we get 100. Arm 2 is a Bernoulli where with probability 0.55 the reward is 2 else the reward is 0. Arm 3 is a Bernoulli where with probability 0.5 it gets 1, else it gets 0. Select all that are true.

- Arm 1 has a mean reward μ_1 of 2, Arm 2 has a mean reward μ_2 of 1.1 and Arm 3 has a mean reward μ_3 of .5
- p_{i_1} selects a2 with probability 0.2 and a3 with probability 0.8. Its mean reward is: $0.2 * \mu_2 + 0.8\mu_3$
- p_{i_2} selects a1 with probability 0.5 and a2 with probability 0.5. Its mean reward is: $0.5 * \mu_1 + 0.5\mu_2$

$$V^{\pi_2} > V^{\pi_1}$$

Importance Sampling (IS) for RL Policy Evaluation

- Let h_j be episode j (history) of states, actions and rewards

$$h_j = (s_{j,1}, a_{j,1}, r_{j,1}, s_{j,2}, a_{j,2}, r_{j,2}, \dots, s_{j,L_j}(\text{terminal}))$$

$\swarrow$
length

Importance Sampling (IS) for Policy Evaluation

- Let h_j be episode j (history) of states, actions and rewards

$$h_j = (s_{j,1}, a_{j,1}, r_{j,1}, s_{j,2}, a_{j,2}, r_{j,2}, \dots, s_{j,L_j}(\text{terminal}))$$

could not
have made
that error

Markov

$$p(h_j | \pi, s = s_{j,1}) = p(a_{j,1} | s_{j,1}) p(r_{j,1} | s_{j,1}, a_{j,1}) p(s_{j,2} | s_{j,1}, a_{j,1})$$
$$p(a_{j,2} | s_{j,2}) p(r_{j,2} | s_{j,2}, a_{j,2}) p(s_{j,3} | s_{j,2}, a_{j,2}) \dots$$

$$= \prod_{t=1}^{L_j-1} p(a_{j,t} | s_{j,t}) p(r_{j,t} | s_{j,t}, a_{j,t}) p(s_{j,t+1} | s_{j,t}, a_{j,t})$$

policy up to h could be h up to t

$$= \prod_{t=1}^{L_j-1} \pi(a_{j,t} | s_{j,t}) p(r_{j,t} | s_{j,t}, a_{j,t}) p(s_{j,t+1} | s_{j,t}, a_{j,t})$$

Importance Sampling (IS) for Policy Evaluation

- Let h_j be episode j (history) of states, actions and rewards, where the actions are sampled from π_2

$$h_j = (s_{j,1}, a_{j,1}, r_{j,1}, s_{j,2}, a_{j,2}, r_{j,2}, \dots, s_{j,L_j}(\text{terminal}))$$

$\sum_{i=1}^{L_j} \text{rewards}$
 $\downarrow$
 h_j

$$V^{\pi_1}(s) \approx$$

$$\frac{1}{n} \sum_{j=1}^n \frac{p(h_j | \pi_1, s)}{p(h_j | \pi_2, s)} G(h_j)$$

$$= \frac{1}{n} \sum_{j=1}^N \prod_{t=1}^{L_j} \frac{p(a_t | \pi_1, s_t)}{p(a_t | \pi_2, s_t)} \frac{p(s_{t+1} | h_t)}{p(s_{t+1} | h_t)} \frac{p(r_t | h_t)}{p(r_t | h_t)} G(h_j)$$

$h \sim \pi_2$

$$= \frac{1}{N} \sum_{j=1}^N \prod \frac{\pi_1(a_t | s_t)}{\pi_2(a_t | s_t)} G(h_j)$$

don't need explicit dyn or reward

Importance Sampling (IS) for Policy Evaluation

- Let h_j be episode j (history) of states, actions and rewards, where the actions are sampled from π_2

$$h_j = (s_{j,1}, a_{j,1}, r_{j,1}, s_{j,2}, a_{j,2}, r_{j,2}, \dots, s_{j,L_j}(\text{terminal}))$$

$$\begin{aligned} V^{\pi_1}(s) &\approx \frac{1}{n} \sum_{j=1}^n \frac{p(h_j|\pi_1, s)}{p(h_j|\pi_2, s)} G(h_j) \\ &= \frac{1}{n} \sum_{j=1}^n \prod_{t=1}^{L_j-1} \frac{\pi_1(a_{j,t}|s_{j,t})p(r_{j,t}|s_{j,t}, a_{j,t})p(s_{j,t+1}|s_{j,t}, a_{j,t})}{\pi_2(a_{j,t}|s_{j,t})p(r_{j,t}|s_{j,t}, a_{j,t})p(s_{j,t+1}|s_{j,t}, a_{j,t})} G(h_j) \\ &= \frac{1}{n} \sum_{j=1}^n \prod_{t=1}^{L_j-1} \frac{\pi_1(a_{j,t}|s_{j,t})}{\pi_2(a_{j,t}|s_{j,t})} G(h_j) \end{aligned}$$

Importance Sampling for Policy Evaluation

- Aim: estimate $V^{\pi_1}(s)$ given episodes generated under policy π_2
 - $s_1, a_1, r_1, s_2, a_2, r_2, \dots$ where the actions are sampled from π_2
- Have access to $G_t = r_t + \gamma r_{t+1} + \gamma^2 r_{t+2} + \gamma^3 r_{t+3} + \dots$ in MDP M under policy π_2
- Want $V^{\pi_1}(s) = \mathbb{E}_{\pi_1}[G_t | s_t = s]$
- IS = Monte Carlo estimate given off policy data
- Model-free method
- Does not require Markov assumption
- Under mild assumptions (coverage and no confounding), unbiased & consistent estimator of V^{π_1}
- Can be used when agent is interacting with environment to estimate value of policies different than agent's control policy

Leveraging Future Can't Influence Past Rewards: PDIS

- Importance sampling (IS):

$$IS(D) = \frac{1}{n} \sum_{i=1}^n \left(\prod_{t=1}^L \frac{\pi_e(a_t | s_t)}{\pi_b(a_t | s_t)} \right) \left(\sum_{t=1}^L \gamma^t r_t^i \right)$$

evaluation / target π

challenge? what are future equiv?

- Per-decision importance sampling (PDIS)

behavior policy generated data

$$PSID(D) = \sum_{t=1}^L \gamma^t \frac{1}{n} \sum_{i=1}^n \left(\prod_{\tau=1}^t \frac{\pi_e(a_\tau | s_\tau)}{\pi_b(a_\tau | s_\tau)} \right) r_t^i$$

- PDIS is unbiased estimator of true value under the same (minimal) assumptions that IS is an unbiased estimator

generally lower variance

Importance Sampling Variance

- Importance sampling, like Monte Carlo estimation, is generally high variance
- Importance sampling is particularly high variance for estimating the return of a policy in a sequential decision process
- Variance can generally scale exponentially with the horizon
 - ① Concentration inequalities like Hoeffding scale with the largest range of the variable
 - ② The largest range of the variable depends on the product of importance weights
 - ③ **Optional check your understanding:** for a H step horizon with a maximum reward in a single trajectory of 1, and if $p(a|s, p_i^b) = .1$ and $p(a|s, p_i) = 1$ for each time step, what is the maximum importance-weighted return for a single trajectory?

Off-policy policy evaluation (revisited)

- Importance sampling (IS):

$$IS(D) = \frac{1}{n} \sum_{i=1}^n w_i \left(\sum_{t=1}^L \gamma^t r_t^i \right)$$

RL this is $\frac{\prod_{t=1}^L \pi_e(a_t|s_t)}{\pi_b(a_t|s_t)}$

- Weighted importance sampling (WIS)

$$WIS(D) = \frac{1}{\sum_{i=1}^n w_i} \sum_{i=1}^n w_i \left(\sum_{t=1}^L \gamma^t r_t^i \right)$$

Weighted Importance Sampling)

- Weighted importance sampling (WIS)

$$WIS(D) = \frac{1}{\sum_{i=1}^n w_i} \sum_{i=1}^n w_i \left(\sum_{t=1}^L \gamma^t r_t^i \right)$$

- Often has much lower variance than IS or PDIS

- Biased. When $n = 1$, $\mathbb{E}[WIS] = V(\pi_b)$

- Strongly consistent estimator of V^{π_e}

- i.e. $\Pr(\lim_{n \rightarrow \infty} WIS(D) = V^{\pi_e}) = 1$
- If

- Finite horizon
- One behavior policy, or bounded rewards

$\frac{1}{\omega_i} \omega_i = 1$
and
overlap
no confounding

Offline Policy Evaluation: What You Should Know

- Be able to define and apply importance sampling for off policy policy evaluation
- Define some limitations of IS (variance)
- Know alternatives that reduce variance without impacting bias (PDIS) or reduce variance while incurring bias (WIS)
- Define why we might want to do batch offline RL policy evaluation and potential applications
- Be aware of the main potential limitations of model and model free methods

- Importance sampling
- Imitation learning
 - Behavior cloning
 - Inverse RL
 - Apprenticeship learning

robotics

Learning from Past Decisions and Outcomes

In some settings there exist very good decision policies and we would like to automate them

- One idea: humans provide reward signal when RL algorithm makes decisions
- Good: simple, cheap form of supervision
- Bad: High sample complexity

Alternative: imitation learning

1999/2000
Shant Russell
Andrew Ng

Reward Shaping

Rewards that are **dense in time** closely guide the agent. How can we supply these rewards?

- **Manually design them:** often brittle
- **Implicitly specify them through demonstrations**



Learning from Demonstration for Autonomous Navigation in Complex Unstructured Terrain, Silver et al. 2010

Examples

- Simulated highway driving [Abbeel and Ng, ICML 2004; Syed and Schapire, NIPS 2007; Majumdar et al., RSS 2017]
- Parking lot navigation [Abbeel, Dolgov, Ng, and Thrun, IROS 2008]



Learning from Demonstrations

- Expert provides a set of **demonstration trajectories**: sequences of states and actions *(no reward) $s_1, a_1, s'_1, a'_1, \dots$*
- Imitation learning is useful when it is easier for the expert to demonstrate the desired behavior rather than:
 - Specifying a reward that would generate such behavior,
 - Specifying the desired policy directly

Problem Setup


- Input:
 - State space, action space
 - Transition model $P(s' | s, a)$
 - No reward function R 
 - Set of one or more teacher's demonstrations $(s_0, a_0, s_1, s_0, \dots)$
(actions drawn from teacher's policy π^*)
- Behavioral Cloning:
 - Can we directly learn the teacher's policy using supervised learning?
- Inverse RL:
 - Can we recover R ?
- Apprenticeship learning via Inverse RL:
 - Can we use R to generate a good policy?

Table of Contents

1 Behavioral Cloning


- Formulate problem as a standard machine learning problem:
 - Fix a policy class (e.g. neural network, decision tree, etc.)
 - Estimate a policy from training examples $(s_0, a_0), (s_1, a_1), (s_2, a_2), \dots$
- Two notable success stories:
 - Pomerleau, NIPS 1989: ALVINN
 - Summut et al., ICML 1992: Learning to fly in flight simulator

ALVINN



Problem: Compounding Errors


Supervised learning assumes iid. (s, a) pairs and ignores temporal structure
Independent in time errors:



Error at time t with probability $\leq \epsilon$

$$\mathbb{E}[\text{Total errors}] \leq \epsilon T$$

Problem: Compounding Errors




Data distribution mismatch!

In supervised learning, $(x, y) \sim D$ during train **and** test. In MDPs:

- Train: $s_t \sim D_{\pi^*}$
- Test: $s_t \sim D_{\pi_\theta}$

A Reduction of Imitation Learning and Structured Prediction to No-Regret Online Learning, Ross et al. 2011

Problem: Compounding Errors



- Error at time t with probability ϵ
- Approximate intuition: $\mathbb{E}[\text{Total errors}] \leq \epsilon(T + (T-1) + (T-2) \dots + 1) \propto \epsilon T^2$
- Real result requires more formality. See Theorem 2.1 in <http://www.cs.cmu.edu/~sross1/publications/Ross-AIStats10-paper.pdf> with proof in supplement: <http://www.cs.cmu.edu/~sross1/publications/Ross-AIStats10-sup.pdf>

A Reduction of Imitation Learning and Structured Prediction to No-Regret Online Learning, Ross et al. 2011

DAGGER: Dataset Aggregation

Initialize $\mathcal{D} \leftarrow \emptyset$.
Initialize $\hat{\pi}_1$ to any policy in Π .
for $i = 1$ **to** N **do** *ignore for now*
 Let $\pi_i = \beta_i \pi^* + (1 - \beta_i) \hat{\pi}_i$.
 Sample T -step trajectories using π_i .
 Get dataset $\mathcal{D}_i = \{(s, \pi^*(s))\}$ of visited states by π_i
 and actions given by expert.
 Aggregate datasets: $\mathcal{D} \leftarrow \mathcal{D} \cup \mathcal{D}_i$.
 Train classifier $\hat{\pi}_{i+1}$ on $\mathcal{D}$.
end for
Return best $\hat{\pi}_i$ on validation.

- Idea: Get more labels of the expert action along the path taken by the policy computed by behavior cloning
- Obtains a stationary deterministic policy with good performance under its induced state distribution
- Key limitation?

Behavioral cloning

- Note: despite these potential limitations, often behavior cloning in practice can work very well, especially if use BCRNN
- See [What Matters in Learning from Offline Human Demonstrations for Robot Manipulation](#). Mandlekar et al. CORL 2021

Today

- Importance sampling
- Imitation learning
 - Behavior cloning
 - Inverse RL

Feature Based Reward Function

- Given state space, action space, transition model $P(s' | s, a)$
- No reward function R
- Set of one or more ~~teacher's~~ ^{expert's} demonstrations $(s_0, a_0, s_1, a_1, \dots)$
(actions drawn from teacher's policy π^*)
- Goal: infer the reward function R
- Assume that the teacher's policy is optimal. What can be inferred about R ?

Check Your Understanding: Feature Based Reward Function

- Given state space, action space, transition model $P(s' | s, a)$
 - No reward function R
 - Set of one or more teacher's demonstrations $(s_0, a_0, s_1, s_0, \dots)$ (actions drawn from teacher's policy π^*)
 - Goal: infer the reward function R
 - Assume that the teacher's policy is optimal.
- 1 There is a single unique R that makes teacher's policy optimal
 - 2 There are many possible R that makes teacher's policy optimal
 - 3 It depends on the MDP
 - 4 Not sure

*∞ horizon
discounted rtt*

Check Your Understanding: Feature Based Reward Function

- Given state space, action space, transition model $P(s' | s, a)$
 - No reward function R
 - Set of one or more teacher's demonstrations $(s_0, a_0, s_1, a_1, \dots)$ (actions drawn from teacher's policy π^*)
 - Goal: infer the reward function R
 - Assume that the teacher's policy is optimal.
- 1 There is a single unique R that makes teacher's policy optimal
 - 2 There are many possible R that makes teacher's policy optimal
 - 3 It depends on the MDP
 - 4 Not sure

Answer: There are an infinite set of R .

Linear Feature Reward Inverse RL

- Recall linear value function approximation
- Similarly, here consider when reward is linear over features
 - $R(s)$ = $\mathbf{w}^T \mathbf{x}(s)$ where $\mathbf{w} \in \mathbb{R}^n, \mathbf{x} : S \rightarrow \mathbb{R}^n$
- Goal: identify the weight vector $\mathbf{w}$ given a set of demonstrations
- The resulting value function for a policy π can be expressed as

$$V^\pi(s_0) = \mathbb{E}_{s \sim \pi} \left[\sum_{t=0}^{\infty} \gamma^t R(s_t) | s_0 \right]$$

Linear Feature Reward Inverse RL

- Recall linear value function approximation
- Similarly, here consider when reward is linear over features
 - $R(s) = \mathbf{w}^T \mathbf{x}(s)$ where $\mathbf{w} \in \mathbb{R}^n, \mathbf{x} : S \rightarrow \mathbb{R}^n$
- Goal: identify the weight vector $\mathbf{w}$ given a set of demonstrations
- The resulting value function for a policy π can be expressed as

$$\begin{aligned} V^\pi(s_0) &= \mathbb{E}_{s \sim \pi} \left[\underbrace{\sum_{t=0}^{\infty} \gamma^t R(s_t)}_{\text{linear value}} \mid s_0 \right] = \mathbb{E}_{s \sim \pi} \left[\sum_{t=0}^{\infty} \gamma^t \underbrace{\mathbf{w}^T \mathbf{x}(s_t)}_{\text{linear value}} \mid s_0 \right] \\ &= \underbrace{\mathbf{w}^T}_{\text{linear value}} \mathbb{E}_{s \sim \pi} \left[\sum_{t=0}^{\infty} \gamma^t \mathbf{x}(s_t) \mid s_0 \right] \\ &= \underbrace{\mathbf{w}^T}_{\text{linear value}} \underbrace{\mu(\pi)}_{\text{linear value}} \end{aligned}$$

- where $\mu(\pi)(s)$ is defined as the discounted weighted frequency of state features under policy π , starting in state s_0 .

Relating Frequencies to Optimality

- Assume $R(s) = \mathbf{w}^T \mathbf{x}(s)$ where $\mathbf{w} \in \mathbb{R}^n, \mathbf{x} : S \rightarrow \mathbb{R}^n$
- Goal: identify the weight vector $\mathbf{w}$ given a set of demonstrations
- $V^\pi = \mathbb{E}_{s \sim \pi} [\sum_{t=0}^{\infty} \gamma^t R^*(s_t) \mid \pi] = \mathbf{w}^T \mu(\pi)$ where
 $\mu(\pi)(s) =$ discounted weighted frequency of state s under policy π .

$\pi \leftarrow \max V^\pi$

$$V^* \geq V^\pi$$

Relating Frequencies to Optimality

- Recall linear value function approximation
- Similarly, here consider when reward is linear over features
 - $R(s) = \mathbf{w}^T \mathbf{x}(s)$ where $\mathbf{w} \in \mathbb{R}^n, \mathbf{x} : S \rightarrow \mathbb{R}^n$
- Goal: identify the weight vector $\mathbf{w}$ given a set of demonstrations
- The resulting value function for a policy π can be expressed as

$$V^\pi = \mathbf{w}^T \mu(\pi)$$

- $\mu(\pi)(s) =$ discounted weighted frequency of state s under policy π .

$$\mathbb{E}_{s \sim \pi^*} \left[\sum_{t=0}^{\infty} \gamma^t R^*(s_t) \mid \pi^* \right] = V^* \geq V^\pi = \mathbb{E}_{s \sim \pi} \left[\sum_{t=0}^{\infty} \gamma^t R^*(s_t) \mid \pi \right] \quad \forall \pi$$

$\mathbf{w}^{*T} \mu(\pi^*) \geq \mathbf{w}^{*T} \mu(\pi)$

- Therefore if the expert's demonstrations are from the optimal policy, to identify $\mathbf{w}$ it is sufficient to find $\mathbf{w}^*$ such that

$$\mathbf{w}^{*T} \mu(\pi^*) \geq \mathbf{w}^{*T} \mu(\pi), \forall \pi \neq \pi^*$$

Feature Matching

- Want to find a reward function such that the expert policy outperforms other policies.
- For a policy π to be guaranteed to perform as well as the expert policy π^* , sufficient if its discounted summed feature expectations match the expert's policy [Abbeel & Ng, 2004].
- More precisely, if

$$\|\mu(\pi) - \mu(\pi^*)\|_1 \leq \epsilon$$

then for all w with $\|w\|_\infty \leq 1$:

$$|w^T \mu(\pi) - w^T \mu(\pi^*)| \leq \epsilon$$

- There is an infinite number of reward functions with the same optimal policy.
- There are infinitely many stochastic policies that can match feature counts
- Which one should be chosen?

- Many different approaches
- Two of the key papers are:
 - Maximum Entropy Inverse Reinforcement Learning (Ziebart et al. AAAI 2008)
 - Generative adversarial imitation learning (Ho and Ermon, NeurIPS 2016)

Summary

- Imitation learning can greatly reduce the amount of data need to learn a good policy
- Challenges remain and one exciting area is combining inverse RL / learning from demonstration and online reinforcement learning
- For a look into some of the theory between imitation learning and RL, see Sun, Venkatraman, Gordon, Boots, Bagnell (ICML 2017)

Imitation learning: What You Should Know

- Define behavior cloning and how it differs from reinforcement learning
- Understand when behavior cloning might be worse than offline reinforcement learning
-

Class Structure

- Last time: Learning from offline data, overview and policy evaluation
- This time: Learning from offline data, policy evaluation and imitation learning
- Next time: Learning from offline data, policy optimization / learning