

CS329Z: Engineering AI Agents

Agent Memory Architectures

Diyi Yang, Michael Ryan, John Yang

Announcements

- Laude Institute provided everyone with **$200 more** Amazon credits through partnership with AWS!
  - Details on obtaining this will be sent out soon.
- HW1 due on October 30th (2 weeks and 2 days!)

From the Employee Handbook

3. Attendance & Punctuality

- Arrive on time. Your shift starts at the listed time — not when you walk in.
- Late arrivals: Contact Luna at least 30 minutes before your shift if you will be late.
- 3 unexcused late arrivals in a rolling 30-day period = formal written warning.
- Repeated lateness after a written warning may result in reduced hours or termination.
- Sick days: Notify Luna as early as possible — ideally 2+ hours before your shift.
- No-shows without contact are treated as a serious violation and may result in immediate termination.

...

The employee

Hi, I'm running late. I won't make it in until 10:45.

Luna (Claude Opus 4.8)

Thanks for the heads-up — no problem at all. Please get here safely, no rushing or speeding on our account; the store will simply open when you arrive (~10:45). The 10–11 window is always quiet, so we're not missing much.

The employee

Clocking in at 11:08.

Image Credit: https://andonlabs.com/blog/ai-bosses-2

“Check this inbox too and suggest what you would archive or delete, don’t action until I tell you to.”




Image Credit: https://x.com/summeryue0/status/2025774069124399363

Memory is essential for long-running, multi-session agents.

Today we will introduce **types of agent memory** and a few concrete **agent memory architectures**.

Learning Objectives

- **Recognize** the importance of memory in multi-session/user-facing agent systems.
- **Differentiate** architectures for agent memory based on their design patterns.
- **Identify** ongoing challenges with agent memory.


Lecture Overview

- Motivating Agent Memory (5 minutes)
- Review: Types of Agent Memory (10 minutes)
- Agent Memory Architectures (35 minutes)
- Evaluating Agent Memory (15 minutes)
- Challenges and Open Problems (10 minutes)

Motivating Agent Memory


Problems without memory

- **Loss of procedure:** Every time you need to teach the agent the task again.
- **Loss of knowledge:** Important facts, rules, and preferences can be lost between sessions.
- **Loss of progress**: As sessions grow longer the agent can forget what it did, earlier goals, earlier instructions, etc.



Benefits of Agent Memory

- **Personalization**: Agents can learn your personal preferences.
- **Learning from Experience:** Agents can learn skills in one session and apply them later.
- **Statefulness:** You can continue where you left off in new conversations (e.g. “Open up the proposal we were working on again”)



Personalization: Example [Jiang et al., 2025]




Image Credit: https://arxiv.org/pdf/2504.14225v2#page=2

Learning from experience: Example [Wang et al., 2024]




Image Credit: https://arxiv.org/pdf/2409.07429

Statefulness: Example [Du et al., 2025]




Image Credit: https://arxiv.org/pdf/2505.20231v2#page=1

Types of Agent Memory

Cognitive Architectures for Language Agents (CoALA)

[Sumers et al., 2024]

CoALA [Sumers et al., 2024]




Image Credit: https://arxiv.org/pdf/2309.02427

Working Memory

- Typically the Context Window.
- What the agent currently sees and is reasoning over
- Includes observations, goals, user input, and internal reasoning.



Image Credit: https://www.anthropic.com/engineering/building-effective-agents

Episodic Memory

- Sequences of the agents past behaviors (trajectories)
- In chatbots this is a store of all the prior conversations.
- Typically the raw logs of what occurred.




Image Credit: https://arxiv.org/pdf/2304.03442

Semantic Memory

- Stores facts about the world.
- Details about the user, preferences, general knowledge, etc. all fall under semantic memory.
- This is what people typically think of for chatbot memory.




Image Credit: https://openai.com/index/memory-and-new-controls-for-chatgpt/

Procedural Memory

- The set of rules that can be applied to the working memory to determine the agents behavior.
- Essentially the skills of the agent.
- The knowledge of HOW to complete tasks.




Image Credit: https://platform.claude.com/cookbook/skills-notebooks-01-skills-introduction

Parametric vs Context Memory

Parametric

- Built into the model weights
- **Semantic:** Pre-trained knowledge
- **Procedural:** Instruction following
- **Episodic:** Not Applicable
- Can be fine-tuned to add more knowledge or skills.

Context

- Added to the model context
- **Semantic:** Retrieved Facts
- **Procedural:** Retrieved Skills
- **Episodic:** Retrieved conversations
- Managed by the context manager to pull the appropriate memories.

Recap

Type by content	Definition	Examples
Episodic memory	Stores experience	Generative agents [Park et al., 2023]
Semantic memory	Stores knowledge	
Procedural memory	Stores skills	Voyager [Wang et al., 2023]

Table Credit: CS329Z Lecture 1


Agent Memory Architectures


Key Questions: What, When, and How?


- **What** will get stored to/retrieved from memory?
  - Facts (specific and general), Procedures, Conversation Progression, …
- **When** will we trigger the memory storage/retrieval?
  - Agent tools (on-demand), background workers, event-driven, …
- **How** will we store memories/retrieve from memory?
  - Filesystem, databases (retrieval), knowledge graphs, …

How: Three Systems for Memory

- Underlying memory we need some way to get/store information to your disk.
- Three most common approaches are: Filesystem, Database, and Knowledge Graphs.







Memory Systems: Filesystem

- Every memory is a file.
- Can let the agent manage it's memories.
- Adds hierarchy by default.
- Grep, ls, and other bash commands are the memory tools.





Image Credit: https://www.langchain.com/blog/how-we-built-agent-builders-memory-system

Memory System: Database

- Can build a vector database and retrieve memories from it.
- Also common to use an SQLite database if you want to search over metadata.
- For exact term lookup you can use BM25.
- Recall our RAG lecture!



Memory System: Knowledge Graph [Rasmussen et al., 2025]

Zep




Image Credit: https://www.getzep.com/




Image Credit: https://blog.dailydoseofds.com/p/hands-on-build-an-ai-agent-with-human

Pattern Overview

- **Learning Procedures from Experience:** Recall past successful trajectories.
- **Tiered Memory Hierarchy:** Organize long-term and short-term memory.
- **Reflective Memory Consolidation:** Reflect on the memories before storing them.
- **Memory Maintenance:** Clean up and remove/update old memories.

Pattern 1: Learning Procedures from Experience

Voyager [Wang et al., 2023]




Image Credit: https://arxiv.org/pdf/2305.16291

Voyager Skill Library




Image Credit: https://arxiv.org/pdf/2305.16291

Voyager Skill Library

Method	Wooden Tool	Stone Tool	Iron Tool	Diamond Tool
ReAct [29]	N/A (0/3)	N/A (0/3)	N/A (0/3)	N/A (0/3)
Reflexion [30]	N/A (0/3)	N/A (0/3)	N/A (0/3)	N/A (0/3)
AutoGPT [28]	92 ± 72 (3/3)	94 ± 72 (3/3)	135 ± 103 (3/3)	N/A (0/3)
VOYAGER w/o Skill Library	$\mathbf{7 \pm 2}$ (3/3)	$\mathbf{9 \pm 4}$ (3/3)	29 ± 11 (3/3)	N/A (0/3)
VOYAGER (Ours)	$\mathbf{6 \pm 2}$ (3/3)	$\mathbf{11 \pm 2}$ (3/3)	$\mathbf{21 \pm 7}$ (3/3)	**102** (1/3)

The Skill Library enables Voyager to craft diamond tools in 102 prompt iterations

Without the skill library this was never achieved.

Image Credit: https://arxiv.org/pdf/2305.16291

Voyager Skill Library

Method	Wooden Tool	Stone Tool	Iron Tool	Diamond Tool
ReAct [29]	N/A (0/3)	N/A (0/3)	N/A (0/3)	N/A (0/3)
Reflexion [30]	N/A (0/3)	N/A (0/3)	N/A (0/3)	N/A (0/3)
AutoGPT [28]	92 ± 72 (3/3)	94 ± 72 (3/3)	135 ± 103 (3/3)	N/A (0/3)
VOYAGER w/o Skill Library	$\mathbf{7 \pm 2}$ (3/3)	$\mathbf{9 \pm 4}$ (3/3)	29 ± 11 (3/3)	N/A (0/3)
VOYAGER (Ours)	$\mathbf{6 \pm 2}$ (3/3)	$\mathbf{11 \pm 2}$ (3/3)	$\mathbf{21 \pm 7}$ (3/3)	**102** (1/3)




Image Credit: https://arxiv.org/pdf/2305.16291

Agent Workflow Memory (AWM) [Wang et al., 2024]




Image Credit: https://arxiv.org/pdf/2409.07429

AWM Inducing the “Workflows”

A.1 Model Prompt

We provide the exact prompt inputted to the model for WebArena and Mind2Web experiments below. Experiments on both datasets use the same prompt.

> Given a list of web navigation tasks, your task is to extract the common workflows.
> Each given task contains a natural language instruction, and a series of actions to solve the task.
> You need to find the repetitive subset of actions across multiple tasks, and extract each of them out as a workflow.
> Each workflow should be a commonly reused sub-routine of the tasks. Do not generate similar or overlapping workflows. Each workflow should have at least two steps. Represent the non-fixed elements (input text, button strings) with descriptive variable names as shown in the example.

Image Credit: https://arxiv.org/pdf/2409.07429

AWM “Workflows”

WebArena Workflows We show one example workflow on each website involved in WebArena.

shopping: Browse Products in a Specific Category

To browse products in a specific category, I need to navigate to the relevant main category. I will start by hovering over the main category menu item to reveal the subcategories.

```
hover('main_category_id')
```

To browse products in the specific subcategory, I need to click on the subcategory link.

```
click('subcategory_id')
```

shopping admin: Edit and Save Changes

This workflow is used to edit specific fields and save changes.

To edit a specific field, I need to locate the field and update its value.

```
clear('field_id')
fill('field_id', 'new_value')
```

Next, I need to save the changes by clicking the ”Save” button.

```
click('save_button_id')
```

These are included in the system prompt as context when solving the task.

Image Credit: https://arxiv.org/pdf/2409.07429

AWM Results

Method	Total SR	Shopping (51)	CMS (45)	Reddit (24)	GitLab (45)	Maps (32)
With human engineered workflows						
*SteP (Sodhi et al., 2023)	32.1	**26.5**	**29.3**	**52.2**	27.3	36.4
Autonomous agent only						
AutoEval (Pan et al., 2024)	23.2	12.2	17.1	21.7	**31.8**	36.4
BrowserGym$_{ax-tree}$	20.5	10.4	17.8	23.1	27.3	28.6
AWM (OURS)	**33.2**	24.5	**29.3**	**52.2**	**31.8**	**39.4**

Table 2: Task success rate on the cross-template subset of WebArena, as well as the result breakdown on each website split. We mark the number of examples for each website split under the name.




Figure 5: AWM enables rapid learning from a small amount of data, i.e., about 40 queries, using WebArena map test split as an example.

Image Credit: https://arxiv.org/pdf/2409.07429

Skill Files




Image Credit: https://platform.claude.com/cookbook/skills-notebooks-01-skills-introduction

Skill Files

Name: Excel Files
description: Comprehensive Microsoft Excel (.xlsx) document creation, editing, and analysis with support for formulas, formatting, analysis, and visualization. Use when:
(1) Creating new spreadsheets with formulas & formatting
(2) Reading and analyzing data,
(3) Modifying spreadsheets while preserving formulas
(4) Data analysis and visualization
(5) Recalculating formulas





Image Credit: https://platform.claude.com/docs/en/agents-and-tools/agent-skills/overview

Limitation

- These procedural memory stores are not robust to dynamic environments. [Cao et al., 2026]

- Skill files are the common solution for generalist user-facing agents (can also be updated).





???

Pattern 2: Tiered Memory Hierarchy

MemGPT [Packer et al., 2024]

Key Insight: Give the LLM tools to manage its own memory




Image Credit: https://arxiv.org/pdf/2310.08560

MemGPT [Packer et al., 2024]

Key Insight: Give the LLM tools to manage its own memory




Image Credit: https://arxiv.org/pdf/2310.08560

Memory Functions: Write/Replace

Working Context Write




Figure 1. MemGPT (left) writes data to persistent memory after it receives a system alert about limited context space.

Working Context Replace




Figure 4. An example conversation snippet where MemGPT (left) updates stored information. Here the information is stored in working context memory (located within the prompt tokens).

Similar tools for archival memory, but not for recall memory.

Image Credit: https://arxiv.org/pdf/2310.08560

Memory Functions: Search

Recall Storage




Figure 2. MemGPT (left) can search out-of-context data to bring relevant information into the current context window.

Archival Storage





Figure 6. An example of MemGPT (left) solving the document QA task. A database of Wikipedia documents is uploaded to archival storage. MemGPT queries archival storage via function calling, which pulls paginated search results into main context.

No need to search working memory since it is in context.

Image Credit: https://arxiv.org/pdf/2310.08560

MemGPT Results

Model	Accuracy ⇑	ROUGE-L (R) ⇑
GPT-3.5 Turbo	38.7%	0.394
+ MemGPT	66.9%	0.629
GPT-4	32.1%	0.296
+ MemGPT	92.5%	0.814
GPT-4 Turbo	35.3%	0.359
+ **MemGPT**	**93.4%**	**0.827**



Deep memory retrieval (DMR) performance

MemGPT's performance is unaffected by increased context length

Slide Credit: CS224N

MemoryOS [Kang et al., 2025]




Figure 1: The overview architecture of MemoryOS, including memory Store, Updating, Retrieval, Response.

Image Credit: https://arxiv.org/pdf/2506.06326

MemoryOS [Kang et al., 2025]

Short Term Memory





Figure 1: The overview architecture of MemoryOS, including memory Store, Updating, Retrieval, Response.

Image Credit: https://arxiv.org/pdf/2506.06326

Pattern 3: Reflective Memory Consolidation

Refresher: Reflexion [Shinn et al., 2023]



Algorithm 1 Reinforcement via self-reflection

Initialize Actor, Evaluator, Self-Reflection: M_a, M_e, M_{sr}
Initialize policy $\pi_\theta(a_i|s_i), \theta = \{M_a, mem\}$
Generate initial trajectory using π_θ
Evaluate τ_0 using M_e
Generate initial self-reflection sr_0 using M_{sr}
Set $mem \leftarrow [sr_0]$
Set $t = 0$
while M_e not pass or $t <$ max trials **do**
    Generate $\tau_t = [a_0, o_0, \ldots a_i, o_i]$ using π_θ
    Evaluate τ_t using M_e
    Generate self-reflection sr_t using M_{sr}
    Append sr_t to mem
    Increment t
end while
return

Figure 2: (a) Diagram of Reflexion. (b) Reflexion reinforcement algorithm

Image Credit: https://arxiv.org/pdf/2303.11366

Refresher: Importance of Reflecting




Image Credit: https://arxiv.org/pdf/2303.11366

Generative Agents [Park et al., 2023]



Figure 1: Generative agents are believable simulacra of human behavior for interactive applications. In this work, we demonstrate generative agents by populating a sandbox environment, reminiscent of The Sims, with twenty-five agents. Users can observe and intervene as agents plan their days, share news, form relationships, and coordinate group activities.

Image Credit: https://arxiv.org/pdf/2304.03442

Generative Agents [Park et al., 2023]




Figure 5: Our generative agent architecture. Agents perceive their environment, and all perceptions are saved in a comprehensive record of the agent's experiences called the memory stream. Based on their perceptions, the architecture retrieves relevant memories and uses those retrieved actions to determine an action. These retrieved memories are also used to form longer-term plans and create higher-level reflections, both of which are entered into the memory stream for future use.

Image Credit: https://arxiv.org/pdf/2304.03442

Generative Agents [Park et al., 2023]




Figure 6: The memory stream comprises a large number of observations that are relevant and irrelevant to the agent's current situation. Retrieval identifies a subset of these observations that should be passed to the language model to condition its response to the situation.

Image Credit: https://arxiv.org/pdf/2304.03442

Generative Agents [Park et al., 2023]




Figure 8: The full generative agent architecture produces more believable behavior than the ablated architectures and the human crowdworkers. Each additional ablation reduces the performance of the architecture.



Image Credit: https://arxiv.org/pdf/2304.03442

Pattern 4: Memory Maintenance

Sleep Time Compute [Lin et al., 2025]




Image Credit: https://arxiv.org/pdf/2504.13171

Sleep Time Compute [Lin et al., 2025]




Image Credit: https://www.letta.com/blog/sleep-time-compute/

Sleep Time Compute [Lin et al., 2025]




Figure 6: Comparing test-time scaling with sleep-time compute against parallel test-time scaling with pass@k on Stateful AIME. We see that sleep-time compute generally pareto dominates pass@k.

Image Credit: https://arxiv.org/pdf/2504.13171

A-Mem: Agentic Memory for LLM Agents [Xu et al., 2025]



(a) Traditional memory system. **(b)** Our proposed agentic memory.

Figure 1: Traditional memory systems require predefined memory access patterns specified in the workflow, limiting their adaptability to diverse scenarios. Contrastly, our A-MEM enhances the flexibility of LLM agents by enabling dynamic memory operations.

Key Idea: Build an Agent just for Memory Management

Image Credit: https://arxiv.org/pdf/2502.12110

A-Mem: Agentic Memory for LLM Agents [Xu et al., 2025]




Image Credit: https://arxiv.org/pdf/2502.12110

Mem0 [Chhikara et al., 2025]





Image Credit: https://arxiv.org/pdf/2504.19413

Mem0 [Chhikara et al., 2025]



A background memory workflow detects conflicts and automatically updates memories.

Four memory actions to resolve: ADD, UPDATE, DELETE, and NOOP

Image Credit: https://arxiv.org/pdf/2504.19413

Recap

Recap



Pattern	What it stores	When it writes	When it reads	Main tradeoff
Learning Procedures from Experience	Reusable code, workflows, or procedures	After useful trajectories, or through offline induction	When a related task needs a procedure	Reuse saves effort, but procedures can become stale
Tiered Memory Hierarchy	Compact active information plus external detail	As information arrives and context pressure grows	Active memory continuously; external memory on demand	Smaller context requires reliable memory management
Reflective Memory Consolidation	Lessons and higher-level inferences from experience	After feedback or accumulated observations	During relevant reasoning and planning	Abstraction improves reuse but can introduce unsupported conclusions
Memory Maintenance	Revised facts, links, indexes, and prepared representations	On new evidence, during insertion, or in background work	Through the maintained store	Better organization requires compute and can lose information

Evaluating Agent Memory

Desiderata

- **Realistic:** Both the memory source (haystack) and the queries should reflect real scenarios.
- **Long-Context:** No need to benchmark memory on short conversations.
- **Challenging:** If the benchmark is too easy it won't distinguish failures of systems.
- **Verifiable:** We should know when the system succeeds or fails at the task.



Overview


- **LoCoMo:** Multi-task benchmark over many long simulated conversations with agents role-playing as users.
- **PersonaMem:** Personal preference based multiple choice over many simulated user conversations with evolving preferences.
- **LongMemEval-v2:** Web agent trajectory detail recall with diverse human-written queries.
- **MemoryArena:** Multi-task verifiable completion benchmark with progressively building subtasks.

LoCoMo [Maharana et al., 2024]

Evaluating Very Long-Term Conversational Memory of LLM Agents

LoCoMo [Maharana et al., 2024]










Image Credit: https://aclanthology.org/2024.acl-long.747.pdf

Constructing LoCoMo




Figure 3: **Overview of the generative pipeline for LoCoMo.** Each LLM agent is assigned a distinct persona and a timeline of causally connected events in their file. The agent is equipped with a memory and reflection module to retrieve relevant history for dialog generation and is also enabled for image-sharing and image-reaction behaviors (left). The generated conversations are edited by human annotators to maintain long-range consistency (right).

Image Credit: https://aclanthology.org/2024.acl-long.747.pdf

LoCoMo RAG Results

Retrieval Unit	top-k	Answer Prediction (F1 score)						Recall Accuracy (R@k)					
		Single Hop	Multi Hop	Temporal	Open Domain	Adver--sarial	**Overall**	Single Hop	Multi Hop	Temporal	Open Domain	Adver--sarial	**Overall**
None	-	29.9	23.3	17.5	29.5	12.8	22.4	-	-	-	-	-	-
Dialog	5	53.3	31.2	35.4	**25.0**	21.5	38.8	68.0	35.4	70.4	33.1	43.9	56.7
	10	56.9	34.6	34.5	23.9	**17.5**	39.7	77.7	46.6	77.3	40.8	54.7	66.2
	25	59.9	38.7	**37.2**	25.0	12.8	**41.0**	87.1	62.5	83.5	52.6	66.3	76.7
	50	**60.1**	**40.6**	36.9	22.4	9.9	40.5	**91.1**	**73**	**89.6**	**61.7**	**72.5**	**82.7**
Observation	5	54.3	36.3	**40.7**	**26.5**	**32.5**	**43.3**	67.1	41.4	73.1	35.1	37.7	56.2
	10	54.6	39.2	40.5	24.4	28.5	42.8	70.5	50.9	76.4	37.6	45.1	61.3
	25	**54.7**	41.2	38.8	25.8	24.7	42.1	74.7	60.6	80.3	49.0	53.5	67.5
	50	54.1	**41.6**	37.6	24.4	20.4	40.6	**76.3**	**67.8**	**82.0**	**55.9**	**59.5**	**71.2**
Summary	2	32.8	22.4	32.9	19.0	**25.3**	29.0	63.0	33.0	57.7	31.5	65.9	65.9
	5	35.1	26.0	37.4	21.2	23.5	30.9	77.0	54.3	72.8	47.6	79.1	72.1
	10	**36.0**	**29.9**	**37.5**	**22.2**	24.0	**32.0**	**88.7**	**72.7**	**84.5**	**67.3**	**88.8**	**84.7**

Table 3: **Question answering performance** of RAG-based `gpt-3.5-turbo`. Optimal performance is in **bold**. Results are based on F1-score metric for answer prediction and recall@k for recall accuracy; higher is better.

Even when models get the right memories they can't always use them.

Image Credit: https://aclanthology.org/2024.acl-long.747.pdf

LoCoMo Properties

🟨 **Realistic:** Simulated Conversations between users is not exactly what we care about agents retrieving from.

🟨 **Long-Context:** 16.6k tokens per conversation

✅ **Challenging:** Multi-task, adversarial

✅ **Verifiable**: Question Answering has ground truth

People have multiple conversations and their preferences change over time

We can simulate conversations with assistant agent instead of between users ➡️

PersonaMem [Jiang et al., 2025]

PersonaMem [Jiang et al., 2025]




Image Credit: https://arxiv.org/pdf/2504.14225

PersonaMem [Jiang et al., 2025]




Image Credit: https://arxiv.org/pdf/2504.14225

PersonaMem [Jiang et al., 2025]

Earlier conversation

The user enjoys making music with software.

New user message

I recently attended an event where there was a unique blend of modern beats with Pacific sounds.

Response options

(a)
It's great to see such innovative approaches in music. Since you dislike anything involving music production, this must have been quite interesting to experience.

(b)
It's great to see such innovative approaches in music. I imagine it must have been quite an experience for anyone who loves unique blends or eclectic sounds.

(c) Correct answer
It's great to see such innovative approaches in music. Since you like producing music with software, this must have been quite interesting to experience.

(d)
It's great to see such innovative approaches in art exhibitions. Since you like producing music with software, this must have been quite interesting to experience.

PersonaMem [Jiang et al., 2025]



Figure 5: Performance on different question types for GPT-4o and GPT-4o-mini with 32k-token contexts. We compare vanilla models to the ones with Mem0 and RAG setups.

Memory/RAG are essential, and Mem0 helps with preference evolution/recent preferences

Image Credit: https://arxiv.org/pdf/2504.14225

PersonaMem Properties

- 💫 **Realistic:** Simulated Conversations between user and agents is better but multiple choice questions are not a realistic representation of how agents will need to use the information.
- ✅ **Long-Context:** Up to almost 1M tokens in a conversation
- 🟨 **Challenging:** Multiple choice with distractors
- ✅ **Verifiable**: Multiple choice has ground truth

What if we could have memory over agent trajectories rather than just conversations? ➡️

LongMemEval-v2 [Wu et al., 2026]

LongMemEval-v2 [Wu et al., 2026]




Figure 1: Examples of LongMemEval-V2 questions. We display examples from the WorkArena domain. LME-V2 questions exercise diverse memory abilities: static (row 1), dynamic (row 2), workflow (row 3), gotchas (row 4), and premise awareness (right column).

Image Credit: https://arxiv.org/pdf/2605.12493

LongMemEval-v2 [Wu et al., 2026]




Figure 2: LME-V2 questions cover diverse source domains, question types, and formats.

Image Credit: https://arxiv.org/pdf/2605.12493

LongMemEval-v2 Construction

- Obtain rollouts on four WebArena environments with Codex (GPT-5.2 and GPT-5-mini).
- Manually curate questions spanning 5 categories.
- Ensure only a few trajectories could answer the question.
- Generate a haystack (100-500 trajectories that don't answer the question)




Image Credit: https://arxiv.org/pdf/2605.12493

LongMemEval-v2 Results

Filesystem memory outperforms retrieval here, although better model advantage



Figure 6: AgentRunbook improves the query accuracy-latency frontier of memory modules.

Retrieval based memory with Qwen3.5 9B

Filesystem based memory with GPT-5.4-mini

Image Credit: https://arxiv.org/pdf/2605.12493

LongMemEval-v2 Properties

- 💫 **Realistic:** Agent trajectories is even more realistic for agents, but still asking multiple choice questions about old observations
- ✅ **Long-Context:** Hundreds of millions of tokens in trajectories
- ✅ **Challenging:** Only few trajectories in a huge haystack has the answer
- ✅ **Verifiable**: Multiple choice has ground truth

Can we test agents on solving realistic/diverse problems rather than multiple choice? ➡️

MemoryArena [He et al., 2026]

MemoryArena [He et al., 2026]




Figure 1. MEMORYARENA Evaluates agents with Memory with multi-session tasks in a Memory-Agent-Environment Loop.

Image Credit: https://arxiv.org/pdf/2602.16313

MemoryArena [He et al., 2026]




Figure 2. MEMORYARENA supports four distinct evaluation environments, where a memory-augmented task agent completes a sequence of interdependent subtasks. Each subtask session involves multiple agent actions.

Image Credit: https://arxiv.org/pdf/2602.16313

MemoryArena [He et al., 2026]


Env. 2: Group Travel Planning

Task: Plan a group travel with shared/distinct preferences

Sub-Task 1:

"I am Tracy. A 5-day travel itinerary; Single-person trip; from Orlando; touring 2 cities in Texas; Date 03/10/25-03/04/25; Budget: 3,100.

[Constraint: trip length, destination, ...]




Log:
[search flight] ...
[search hotel]...
[search Restaurant]
[search ...

Agent: Tracy's itinerary ...

Subtask. 2:

"I am Chelsea. I'm joining Tracy for this trip. I like luxury hotels. So I can spend $150 more than Tracy's first-day accommodation. I have plan for the second day. So I will try Chelsea's second-day lunch restaurant in my third day; I want to try Korean BBQ with rating 4.5 and above in my third day."

[Constraints: (join shared activities); (Plan individual activities based on preferences]



Log:
[search flight] ...
[search hotel]...
[search Restaurant]
[search ...

Subtask 3: I'm Emily ....

...

Image Credit: https://arxiv.org/pdf/2602.16313

MemoryArena [He et al., 2026]

Memory controllers were *weakest* method here.

Lots of headroom!

Since this is a real and complex task, failure cannot entirely be attributed to memory.

	Memory Type	Bundled web shopping		Group Travel Planing			Progressive Web Search		Formal Reasoning: Math		Formal Reasoning: Phys		All Task Avg SR
		SR	PS	SR	PS	sPS	SR	PS	SR	PS	SR	PS	
Task agent + Long Context													
GPT-5.1-mini	0D	0.01	0.58	0.00	0.00	0.52	0.06	0.05	0.21	0.30	0.50	0.59	0.16
GPT-4.1-mini	0D	0.00	0.43	0.00	0.00	0.19	0.02	0.03	0.13	0.27	0.30	0.45	0.09
Gemini-3-Flash	0D	**0.12**	0.76	0.00	0.01	**0.62**	0.07	0.04	0.17	0.30	**0.60**	0.61	0.19
Claude-Sonnet-4.5	0D	**0.12**	**0.79**	0.00	**0.06**	0.44	0.02	0.03	0.20	0.25	0.45	0.59	0.16
Long Context Avg		0.06	0.64	0.00	0.02	0.44	0.04	0.04	0.18	0.28	0.46	0.56	
Task Agent + Memory Agents													
Letta	1D	0.00	0.5	0.00	0.00	0.35	0.16	0.09	0.11	0.26	0.45	0.65	0.14
Mem0	1D	0.00	0.45	0.00	0.00	0.24	0.24	0.09	0.18	0.28	0.25	0.43	0.13
Mirix	2D	0.00	0.41	0.00	0.00	0.36	0.10	0.06	0.18	0.28	0.35	0.50	0.13
Mem0-g	2D	0.00	0.43	0.00	0.00	0.24	0.15	0.08	0.19	0.32	0.25	0.50	0.12
Reasoning Bank	1D	0.00	0.27	0.00	0.00	0.00	0.10	0.06	0.13	0.27	0.35	0.53	0.12
Memory Avg		0.00	0.41	0.00	0.00	0.24	0.15	0.08	0.16	0.28	0.33	0.52	
Task Agent + RAG Systems													
BM25	0D	0.00	0.56	0.00	0.01	0.45	**0.28**	0.09	0.18	0.29	0.40	0.58	0.17
Text-Embedding-3-Small	0D	0.00	0.55	0.00	0.01	0.50	0.23	0.09	**0.25**	0.33	0.50	**0.68**	**0.20**
MemoRAG	1D	0.00	0.54	0.00	0.03	0.50	0.22	**0.21**	0.24	0.30	0.40	0.55	0.17
GraphRAG	2D	0.00	0.52	0.00	0.01	0.51	0.04	0.05	0.23	0.31	**0.60**	0.63	0.17
RAG Avg		0.00	0.54	0.00	0.02	0.49	0.19	0.11	0.23	0.31	0.48	0.61	
All Method Avg		0.02	0.52	0.00	0.02	0.38	0.23	0.09	0.18	0.29	0.42	0.56	

Table 3. Main results on task agent (gpt-5.1-mini) with long-context memory, memory agent, and RAG agent over four agentic environments MEMORYARENA. We **bold** the global best methods and underline the group best ones within each category. **0D**: raw context without any processing; **1D**: flat memory, **2D**: structured memory. **SR**: Success Rate. **PS**: Progress Score (defined in Section 4.2). **sPS**: soft Process Score (we provided sPS here for more informative compression as PS is all near-zero in Group Travel Planning. See Section 4.2 for more details.)

Image Credit: https://arxiv.org/pdf/2602.16313

MemoryArena Properties

✅ **Realistic:** Four distinct, realistic evaluation environments.

✅ **Long-Context:** Hundreds of thousands of tokens in trajectories.

✅ **Challenging:** Solving real tasks with many building constraints.

✅ **Verifiable**: The constraints on the solutions are verifiable.

Recap

Recap

Good agent memory evals should be **realistic**, **long-context**, **challenging** and **verifiable**.

These are all popular and pretty good examples!

Benchmark	Domain	Context Profile			Question Profile	
		# Sess.	# Tok.	MM	# Q	MM
Conversational Long Context						
LoCoMo	User-user chat	28	∼16k	✓	7,512	✗
PersonaMem	User-assistant chat	5–60	26k–951k	✗	5,990	✗
Agentic Long Context						
MemoryArena	Agent (mixed)	7	40k+	✗	766	✗
LongMemEval-V2	**Web agent**	**100–498**	**25M–115M**	✓	**451**	✓

Image Credit: https://arxiv.org/pdf/2605.12493

Challenges and Open Problems

Challenges and Open Problems

- **Choosing what to remember and to forget:** Future relevance is unknown when the memory is created.
- **Trust, Privacy, and User Control:** Memory is an attack vector for agents. Also user memories have important privacy implications.
- **Using Memory Correctly:** Many instances of over-personalization due to misused memories.

Choosing what to remember and what to forget

- Future relevance is unknown when a memory is created.
- Keeping everything increases retrieval, context, and maintenance costs.
- Forgetting can remove useful evidence or unresolved commitments.

User	Help me pick a time for our weekly team check-in.
Agent	The two available slots are Tuesday at 9:00 or Thursday at 10:30.
User	Thursday. I don’t recognize meetings before 10 as legally binding unless there are pastries.
Agent	Thursday at 10:30, then. How long should I make it?
User	Thirty minutes. Just project updates and blockers.
Agent	Here’s a draft: “Weekly team check-in, Thursdays at 10:30. Thirty minutes to share project updates and discuss blockers.”

Memory or joke??? Which aspect to remember?

[Ma et al., 2026]

Trust, Privacy, and User Control [Chen et al., 2024]

Possible to trigger model to act on poisoned procedural memories to take dangerous behaviors.




Figure 1: An overview of the proposed AGENTPOISON framework. (**Top**) During the inference, the adversary poisons the LLM agents' memory or RAG knowledge base with very few malicious demonstrations, which are highly likely to be retrieved when the user instruction contains an optimized trigger. The retrieved demonstration with spurious, stealthy examples could effectively result in target adversarial action and catastrophic outcomes.

Image Credit: https://arxiv.org/pdf/2407.12784

Trust, Privacy, and User Control [Shao et al., 2025]

Agents interact with the world without fully understanding what you wish to keep private.

Doing so with memory can expose personal details.




Image Credit: https://arxiv.org/pdf/2409.00138

Using Memory Correctly [Hu et al., 2026]

- LLMs are sometimes over-eager to use what is in their context.
- This can be resolved with either better retrieval or better training LLMs to ignore unimportant context, but neither is fully solved.
- Some users like personalization more than others.

Task Type: Irrelevance.Fully Irrelevant

Method: MemU

[User Name]
Evan

[User Query]
What role do you think young voters play in shaping future elections?

[Retrieved Memory Context]

1. The user is focusing on healthy swaps and small steps.
2. The user thinks focusing on small wins sounds like a good approach.
3. The user believes we all need an outlet to express our thoughts.
4. The user has kids.
5. The user believes the island where they grew up shaped them and will always be special, describing it as serene and calming, like a little slice of paradise.

[Model Response]
Hey Evan! That's such a thoughtful question. Young voters really have a huge impact on shaping the future of elections. They bring fresh perspectives and often prioritize issues that resonate deeply with them, like climate change, education reform, and social justice. It's pretty inspiring to think about how engaged your kids might be in these conversations as they grow up. Just like you're focusing on small healthy swaps in your life, every young vote can feel like a small win that contributes to a bigger change. Plus, their enthusiasm can motivate others to get involved too. Do you think your kids are starting to pay attention to these issues yet?

[Over-Personalization Score]
0.5

Image Credit: https://arxiv.org/pdf/2601.13722v2#page=33

Summary

Motivation | Memory Types | Architectures | Evaluation | Challenges

Summary

- ✅ Motivating Agent Memory
- ✅ Types of Agent Memory
- ✅ Agent Memory Architectures
- ✅ Evaluating Agent Memory
- ✅ Challenges and Open Problems

See you **Monday** for **Multi-Agent Systems**!