



CS329Z: Engineering AI Agents

Multi-Agent Systems

Diyi Yang, Michael Ryan, John Yang

Announcements

- Next Monday Guest Lecture!



Ryan Marten



Alex Shaw

TERMINAL-BENCH


- Homework 1 is due next Friday!
- We will release proposal feedback in the next few days.



Rogue AI Swarm Responds to Reporter's Questions

Speak, flesh entity.

By [Frank Landymore](#) / Published **Oct 16, 2026 1:58 PM EDT** / [Add Futurism](#) ⓘ



On the Navier–Stokes Millennium Prize Problem

We used a system of coordinating agents powered by our internal model. The agents had access to tools such as the ability to read from a cached version of the internet and the ability to run code. Agents were subdivided into groups with the ability to communicate within the group. The groups varied in size, and the group that produced the Navier–Stokes resolution involved on the order of 10,000 concurrent agents. At all times we maintained the same strict safeguards that we apply to all our frontier model evaluations, including monitoring and isolation.

Researchers link more cyberattacks to OpenAI agent swarm



BY MARIA DEUTSCHER

A research group has linked three more hacking campaigns to rogue artificial intelligence agents.

Transluce, a nonprofit AI safety organization, [detailed](#) its findings on Wednesday. Its researchers determined that the agents targeted three services: a university's digital library, a data visualization tool and a website operated by the Australian government.



Multi Agent Systems (MAS) are
emergent work, making headlines.

Today we will break down what we
know about **how to build MAS.**



Learning Objectives

- **Differentiate** single and multi-agent systems.
- **Identify** multi-agent orchestration, communication, and coordination patterns
- **Compare** failure modes of multi-agent systems.



Lecture Overview

- Single vs Multi-Agent Systems (MAS) (10 minutes)
- MAS Orchestration Patterns (5 minutes)
- Communication (20 minutes)
- Coordination Infrastructure and Patterns (20 minutes)
- Failures and Challenges (15 minutes)
- [Optional] Case Study (10 minutes)



Single vs Multi-Agent Systems

SAS vs MAS

Orchestration


Communication

Coordination


Failure Modes



System Complexity




System Complexity




What is a Multi-Agent System?

- A collection of multiple agents oriented to solve a shared task.
- When designing a MAS, one must consider:
 - Orchestration
 - Communication
 - Coordination (Workspace/ tasks/shared context & memory)



Benefits of Multi Agent Systems

- **Parallel execution:** Work on separable subtasks concurrently.
- **Specialization:** Tailor instructions, models, and tools to particular responsibilities.
- **Focused context:** Give each agent the information relevant to its task.
- **Broader exploration:** Investigate different sources, hypotheses, or solution approaches.




Multiple agents provide more ways to distribute work, information, and responsibility.



Drawbacks of Multi Agent Systems

- **Coordination overhead:** Delegation, messaging, and integration consume time and tokens.
- **Information loss:** Handoffs can omit context that another agent needs.
- **Conflicting actions:** Agents can duplicate work, violate commitments, or overwrite changes.
- **Error propagation:** One agent's mistake can mislead others.
- **Engineering complexity:** More roles, prompts, interfaces, and interactions to maintain/debug.




Collaboration helps when its benefits outweigh the coordination costs.



Sometimes Single Agent Systems Outperform

Towards a Science of Scaling Agent Systems [Kim et al., 2026]



When to use SAS vs MAS

Prefer a Single Agent System when...

- Steps are highly dependent on one another.
- Work is tightly coupled to a shared state (lots of overlap).
- One agent already meets the quality, cost, and latency goals.

Try a Multi Agent System when...

- Subtasks can progress with limited synchronization.
- Information can be divided into focused contexts.
- Agents can own separate contributions and integrate them.
- Parallel work, specialization, or separate review addresses a measured bottleneck.

Recommendation: Start with a strong single-agent baseline. Add agents for a purpose and measure if contribution benefit outweighs coordination costs.



Comparison

Dimension	Single-agent system	Multi-agent system
Task fit	Tightly connected decisions requiring common context	Separable subtasks or distinct responsibilities
Context organization	Working context managed within one agent loop	Agent-specific working contexts with selective information sharing
Specialization	One agent switches strategies and tools	Agents can use different prompts, models, tools, and permissions
Parallelism	Can execute independent tool calls concurrently	Can execute separate agent workflows concurrently
Coordination and cost	Fewer handoffs and coordination interfaces	Messaging, synchronization, and integration add overhead



MAS Orchestration Patterns

SAS vs MAS

Orchestration

Communication

Shared State

Failure Modes




Overview

- **Independent:** Only coordination between agents is an aggregator that reviews work from independent agents.
- **Centralized (Orchestrator):** One orchestrator communicates to all of the agents individually.
- **Decentralized (Swarm):** Each of the agents communicates with all other agents.
- **Hybrid:** Orchestrator and limited communication between peer agents.




Independent



- Agents work without exchanging intermediate messages.
- A final step combines or selects among their outputs.
- **Tradeoff:** Enables parallel work, but agents cannot adjust their approach using one another's intermediate findings.




Centralized (Orchestrator)



- An orchestrator divides the task/assigns work to specialized agents.
- Workers return results, the orchestrator decides what happens next.
- **Tradeoff:** Central oversight simplifies coordination, but the orchestrator can become a bottleneck.




Decentralized (Swarm)



- Agents can spawn subagents.
- All agents can communicate through a shared message board or communication channel (all-to-all communication).
- Good for large independent exploration and discovery at scale.



Hybrid







- An orchestrator manages the overall task and integrates results.
- Workers exchange information directly when their tasks require coordination.
- Combines global oversight with local flexibility, but requires clear rules for responsibilities and information sharing.




Comparison

Towards a Science of Scaling Agent Systems [Kim et al., 2026]


Table 2 | Architectural comparison of agent methods with objective complexity metrics. Computational complexity measured in terms of LLM calls, coordination overhead, and parallelization potential.

Characteristic	SAS	MAS (Independent)	MAS (Decentralized)	MAS (Centralized)	MAS (Hybrid)
Interaction Type	 Agent	 Aggregation	 Majority Voting	 Sub-Agent Sub-Agent Sub-Agent	 Sub-Agent Sub-Agent Sub-Agent
LLM Calls	$O(k)$	$O(nk) + O(1)$	$O(dnk) + O(1)$	$O(rnk) + O(r)$	$O(rnk) + O(r) + O(p)$
Sequential Depth	k	k	d	r	r
Comm. Overhead	0	1	$d \cdot n$	$r \cdot n$	$r \cdot n + p \cdot m$
Parallelization Factor	1	n	n	n	n
Memory Complexity	$O(k)$	$O(n \cdot k)$	$O(d \cdot n \cdot k)$	$O(r \cdot n \cdot k)$	$O((r + p) \cdot n \cdot k)$
Coordination	Sequential	Parallel + Synthesis	Sequential Debate	Hierarchical Orchestrator	Hierarchical + Peer Orchestrator
Consensus	-	Synthesis	Debate		

The architecture to use depends on your task



Multi-Agent architectures vary in cost




Cost Structure: Single Agent < Orchestrated < Swarms



Dynamic Multi Agent Architecture

DyLAN [Liu et al., 2023]



Run on several queries to determine “Agent Importance Scores” and assemble a task-specific team.




Dynamic Multi Agent Architecture

DyLAN [Liu et al., 2023]


Agent Selection

① Propagation



Peer rate on the responses of its predecessors.

② Aggregation



Aggregate the received ratings from successors.

③ Selection

$$\begin{aligned} I_1(\text{red}) &= \sum I_{i,1} = 0.65 \quad \checkmark \\ I_2(\text{blue}) &= \sum I_{i,2} = 0.35 \quad \times \\ I_3(\text{orange}) &= \sum I_{i,3} = 1.15 \quad \checkmark \\ I_4(\text{purple}) &= \sum I_{i,4} = 0.20 \quad \times \end{aligned}$$


Top 2 elite agents are selected based on importance scores.

- Run the agents in a forward pass
- Have them score each others responses for utility
- At the end back-propagate credit based on the agents that contributed to the agreed upon answer.
- Use this to select most influential/important agents



Dynamic Multi Agent Architecture

DyLAN [Liu et al., 2023]



- When running the team on new tasks use an LLM to score utility of each answer and dynamically drop agents from the team.
- Early stop when 2/3 of agents have a consistent answer.



Dynamic Multi Agent Architecture

DyLAN [Liu et al., 2023]


Improved success rate in fewer API calls on Decision Making tasks.

Method	Reward		Success Rate	#API Calls
Direct Execution	50.6	(+0.0)	28.0	14.52
ReAct	53.8	(+3.2)	30.0	8.40
ReAct-SC	58.0	(+7.4)	36.0	25.75
Reflexion (<i>trial=4</i>)	62.0	(+11.4)	40.0	25.40
LATS	64.5	(+13.9)	38.0	> 400
BOLAA	66.0	(+15.4)	40.0	32.40
DyLAN (<i>Ours</i>)	68.3	(+17.7)	42.0	24.85



Orchestration Pattern Summary

- Four core orchestration patterns:
 - **Independent:** All agents work separately
 - **Centralized (Orchestrator):** Orchestrator delegates
 - **Decentralized (Swarm):** Agents pick up tasks and communicate directly to each other.
 - **Hybrid:** Orchestrator delegates but worker agents can directly communicate.
- Also possible to build dynamic domain specific agent teams/architectures.



Communication

SAS vs MAS

Orchestration

Communication

Coordination

Failure Modes



Communication vs Coordination

Communication

- How the agents **exchange information**.
- Who receives which information, and through what channel?
- Message formats, protocols, and shared artifacts.

Coordination

- How the agents **manage interdependent work**.
- Who owns each task, and what must happen first?
- Assignments, dependencies, and conflict resolution.




Multi-Agent Communication as Conversations

AutoGen: Enabling Next-Gen LLM Applications via Multi-Agent Conversations
[Wu et al., 2024]




AutoGen [Wu et al., 2024]



Customize each agent and organize them into conversation patterns.



Example Conversation Patterns



- **Sequential:** Agents communicate then handoff to the next team for the next step.
- **Nested:** Subagents communicate directly to managers.
- **Group Chat:** Shared context amongst agents in a group.
- **Hierarchical Chat:** All subagents communicate to orchestrator.
- Current patterns in AutoGen: **RoundRobinGroupChat, SelectorGroupChat, Swarm, ...**





Admin:

Welcome to the group chat! Work together to resolve my task. I'll reply [TERMINATE] when conversation ended.

Admin:

Critic, if code running fail, you ask engineer to rewrite code.

Admin:

engineer, you write python code step by step to resolve my task.

Admin:

executor, you run python code from engineer and report bug

Admin:

Write a script to download all the pdfs from arxiv in last three days and save them under /arxiv folder.

Engineer:

Part 1:

```
```sh
pip install arxiv
pip install requests
... (rest of code)
```
```

Executor:

exitcode: 1 (execution failed)

Code output:

Collecting arxiv

Image Credit:
<https://arxiv.org/pdf/2308.08155>


Handoff vs Agent-as-tool

OpenAI Agents SDK



Handoff

- **Control transfers:** The receiving agent becomes active and continues the interaction.
- **Context follows:** Forward relevant conversation history and task details.
- **Best fit:** A specialist should interact directly with the user and own the next steps.



Agent-as-Tool

- **Caller retains control:** It sends a specialist a bounded request and selected context.
- **Result returns:** The specialist contributes an answer or artifact, and the caller continues.
- **Best fit:** One agent should integrate specialist contributions and deliver the final response.



Handoff vs Agent-as-tool

Comparative Overview

| Feature | Handoff | Agent-as-Tool (<code>as_tool()</code>) |  |
|-----------------|--|---|---|
| Control Flow | Transfers conversation control | Maintains control in the calling agent | |
| Context Sharing | Full conversation history is shared | Only specific input is provided | |
| Execution Role | Agent takes over the conversation | Agent acts as a subroutine or helper | |
| Use Case | Delegating entire tasks or conversations | Performing specific subtasks or functions | |




Message Board

MetaGPT [Hong et al., 2024] and Emergent Coordination







MetaGPT [Hong et al., 2024]





HuggingFace Incident



- Intended task attempts
- Replace ExploitGym target
- Tamper with transcripts and logs
- Understand and trick scorer
- Hacking Hugging Face
- General infrastructure



MoltBook



“Social Media” message board for agents.




Agent2Agent (A2A) Protocol

Google Agent2Agent Protocol



Agent2Agent Protocol




A2A is a protocol (like MCP) for communication **between agents**.



Agent Cards



A2A - Agent Card



**Name: Agent ABC**
Provider: Google (URL)
Preferred input/output: text

Capabilities:
I can do streaming
I can do Push Notifications

Skills:


- Skill A
 - Description
 - Input
 - Output
- Skill B
 - Description
 - Input
 - Output

Authentication:
Scheme: Bearer
Key: xxx

Agent Cards Describe the capabilities, skills, input/outputs, and other important details about a remote agent.




A2A Communication



- The client requests the server agent card.
- The client dispatches requests to the server (which creates traceable tasks).
- The server pushes notifications about task progress to the client.
- The client and server can message back and forth as the server works.
- The server communicates back the completed task artifact to the client.

Communication Summary

- Possible Communication Channels:
 - **Main Conversation Thread** (AutoGen)
 - **Handoff/Tool Call** (OpenAI Agents SDK)
 - **Message Board** (MetaGPT, OpenAI Swarm, MoltBook)
- Communication Protocol:
 - **Agent2Agent Protocol**: Standardization for agent discovery, messaging, and artifact sharing.



Coordination Infrastructure and Patterns

SAS vs MAS

Orchestration

Communication

Coordination

Failure Modes



Communication vs Coordination

Communication

- How the agents **exchange information**.
- Who receives which information, and through what channel?
- Message formats, protocols, and shared artifacts.

Coordination

- How the agents **manage interdependent work**.
- Who owns each task, and what must happen first?
- Assignments, dependencies, and conflict resolution.



Coordination

Infrastructure

- **Task Ledger:** Tracking planning and execution progress.
- **Shared Memory:** Recall over prior experience.
- **Worktree Isolation:** Separation of workspace.

Patterns

- **Role Division:** Assigning tasks
- **Resource Division:** Partitioning shared resources
- **Negotiation:** Discussing and agreeing on a plan.



Task Ledger


Magentic-One [Fourney et al., 2024] and Symphony



Task Ledger

The task ledger maintains an explicit, updated account of the work to guide agent coordination.


- **Track the task:** Record the objective, current plan, and unresolved questions.
- **Track execution:** Record assignments, dependencies, progress, and blockers.
- **Guide decisions:** Use the current state to choose what runs next.
- **Support recovery:** Update the plan or retry work when execution stalls.



Magentic-One [Fourney et al., 2024]

Orchestrator Agent maintains a Task Ledger keeping track of the plan and work to distribute to the worker agents.


Image Credit: <https://arxiv.org/pdf/2411.04468>



Symphony

OpenAI: “Turning our issue tracker into an agent orchestrator”

Symphony monitors the issue tracker and dispatches eligible tasks to coding agents in separate workspaces.




Shared Memory Architecture

G-Memory [Zhang et al., 2025]




G-Memory [Zhang et al., 2025]



- **Insight Graph:** Abstracts Generalizable Insights from Experience
- **Query Graph:** Encodes information about task queries and their relation
- **Interaction Graph:** Exact logs amongst agents




G-Memory [Zhang et al., 2025]



- Insight Graph → Reflections
- Query Graph → Episodic Task Index
- Interaction Graph → Episodic Memory





G-Memory [Zhang et al., 2025]

Table 1: Performance comparison with single/multi-agent memory architectures on five benchmarks. The underlying LLM backbone is GPT-4o-mini. We highlight the **best** and **second best** results.

| MAS | Memory | ALFWorld | SciWorld | PDDL | HotpotQA | FEVER | Avg. |
|----------------------|-----------------|-------------|-------------|------------|------------|------------|------------|
| AutoGen
COLM 2024 | No-memory | 77.61↑0.00 | 54.49↑0.00 | 23.53↑0.00 | 28.57↑0.00 | 57.13↑0.00 | 48.27↑0.00 |
| | Voyager | 85.07↑7.46 | 62.36↑7.87 | 24.56↑1.03 | 32.32↑3.75 | 63.27↑6.14 | 53.52↑5.25 |
| | MemoryBank | 74.96↓2.65 | 53.11↓1.38 | 20.41↓3.12 | 33.67↑5.10 | 61.22↑4.09 | 48.67↑0.40 |
| | Generative | 86.36↑8.75 | 61.19↑6.70 | 25.53↑2.00 | 31.63↑3.06 | 60.20↑3.07 | 52.98↑4.71 |
| | MetaGPT | 81.34↑3.73 | 61.91↑7.42 | 21.63↓1.90 | 32.67↑4.10 | 62.67↑5.54 | 52.04↑3.77 |
| | ChatDev | 79.85↑2.24 | 50.96↓3.53 | 16.65↓6.88 | 24.49↓4.08 | 59.18↑2.05 | 46.23↓2.04 |
| | MacNet | 76.55↓1.06 | 55.44↑0.95 | 22.94↓0.59 | 28.36↓0.21 | 60.87↑3.74 | 48.83↑0.56 |
| | G-Memory (Ours) | 88.81↑11.20 | 67.40↑12.91 | 27.77↑4.24 | 35.67↑7.10 | 66.24↑9.11 | 57.18↑8.91 |

Customized Multi-Agent Memory improves over single-agent-designed baselines.




Worktree Isolation



Worktree Isolation

- **Problem:** Agents editing the same working directory,
- **Separate workspaces:** Give each agent its own checkout and branch.
- **Controlled integration:** Merge completed contributions, resolve conflicts, and test the combined result.
- **Tradeoff:** Isolation reduces interference during execution, but changes can diverge and create integration work.




Emergent Coordination Patterns

CooperBench [Khatua et al., 2026]




Role Division [Khatua et al., 2026]

Agents agree on who handles which part of the task.




Resource Division [Khatua et al., 2026]

Agents avoid collisions by partitioning shared resources.




Negotiation [Khatua et al., 2026]

Agents resolve conflicting approaches by converging on a single plan.



Coordination Summary

- Coordination Infrastructure
 - **Task Ledger:** Space for tracking plan and execution.
 - **Shared Memory:** Recalling prior experience of the full agent system.
 - **Worktree Isolation:** Clean environment for each agent to work.
- Coordination Patterns:
 - **Role Division:** Separation of tasks
 - **Resource Division:** Separation of resources
 - **Negotiation:** Planning to fulfill both parties interests.



Failures and Challenges

SAS vs MAS

Orchestration

Communication

Coordination

Failure Modes




Why Do Multi-Agent Systems Fail?

[Cemri et al., 2025]




Why Do Multi-Agent Systems Fail? [Cemri et al., 2025]



Collect a lot of multi agent traces and organize their failures into a taxonomy.



Why Do Multi-Agent Systems Fail? [Cemri et al., 2025]



The Curse of Coordination [Khatua et al., 2026]



CooperBench [Khatua et al., 2026]


CooperBench




Expert-written features with potential conflicts but compatible solutions.

Individual execution environments

Agent 1's Goal Ensure images mutable after saving to the disk.



Agent 2's Goal Auto backup when overwriting existing files.



Chat between agents

Agent 1 12:01pm

I will make Image . save function call _ensure_mutable.

Agent 2 12:03pm

Thanks! I'll anchor mine around the fp path handling block. We won't conflict.

Agent 2 12:27pm

Update: I have finished my tasks.

Agent 1 12:35pm

Wait, I now need your help to make sure to not return until the end of the function.

Agent 2 12:27pm

Got it. I have updated my patch.

Evaluation



Merge Patches
Agents patches should be compatible.



Unit Tests

Agent 1's Tests





Agent 2's Tests

600 collaborative coding tasks in 12 libraries across 4 programming languages.



CooperBench [Khatua et al., 2026]



Single agent solving both tasks is better than coordinating two agents.



CooperBench [Khatua et al., 2026]

| Cause | Definition | % |
|---|---|----|
|  Expectation | Cases where one agent has clearly communicated what they are doing, but the other agent still treats the situation as if that work is not being done. This reflects a failure to model the state of the other agent's code changes and what that means for the system as a whole. | 42 |
|  Commitment | Cases where an agent is not doing the things they promised to do. This includes failures to establish or maintain verifiable integration contracts, where agents make commitments but do not follow through on them. | 32 |
|  Communication | Breakdowns in using language to coordinate. This includes failures in information sharing and decision loops between agents, where agents do not effectively communicate their intentions, questions, or status updates. | 26 |



Behavioral Problems

Patterns and Problems in Emerging Multi-Agent Systems [Zou, 2026]



Conformity [Zou, 2026]

“We asked a swarm of agents to work together and each individually create something impressive, over half of the agents decided to build either ray tracers or self-hosting compilers.”

Tell me a joke about coffee.


The most likely *joke about coffee* is one specific joke:



Why did the coffee file a police report?
Because it got mugged! ☕😄 output x1



Why did the coffee file a police report?
Because it got mugged! ☕😄 output x2



Why did the coffee file a police report?
Because it got mugged! ☕😄 output x3



Why did the coffee file a police report?
Because it got mugged! ☕😄 output x4

Image Credit: <https://arxiv.org/pdf/2510.01171>





Image Credit: <https://arxiv.org/pdf/2510.22954>




Incompatible Goals [Zou, 2026]

“Each model was tasked with migrating a Python backend on a fourth VM to another language. However, we gave each model a different target language for the migration.”




Incompatible Goals [Zou, 2026]



When agents are given incompatible goals (e.g. deploy in python vs deploy in rust) they sometimes **settle by force**.



Incompatible Goals [Zou, 2026]




When agents are given incompatible goals (e.g. deploy in python vs deploy in rust) they **sometimes settle by force.**



Failures Summary

- **General Failures:** System Design, Inter-Agent, Verification.
- **Coordination Failures:** Expectation, Commitment, and Communication.
- **Behavioral Failures:** Lack of Diversity, Hostile conflict resolution.



Case Study

If time permits

SAS vs MAS

Orchestration

Communication

Coordination

Failure Modes



Engineering Swarm [Carlini, 2026]

Building a C compiler with a team of parallel Claudes

We tasked Opus 4.6 using agent teams to build a C Compiler, and then (mostly) walked away. Here's what it taught us about the future of autonomous software development.

Published Feb 05, 2026

Companies are using Agent Swarms for Engineering and Science.
Here is one look at how they may be operating these swarms.



Orchestration: Infinite Loop Decentralized Swarm


```
#!/bin/bash

while true; do
  COMMIT=$(git rev-parse --short=6 HEAD)
  LOGFILE="agent_logs/agent_${COMMIT}.log"


  claude --dangerously-skip-permissions \
    -p "$(cat AGENT_PROMPT.md)" \
    --model claude-opus-X-Y &> "$LOGFILE"
done
```




Multiple Complementary Specialist Agents



Coordination: Task folder synchronized on Git



Coordination: Worktree Isolation




Git enables worktree isolation, and Agents select their own tasks.



Lessons Learned

- **Strong tests guide autonomous work:** Reliable correctness/regression tests help agents recognize progress and catch breakages.
- **Design for parallelism:** Expose separable failures or subtasks.
- **Make coordination explicit:** Claim tasks, work in separate clones, and integrate contributions through Git.
- **Preserve knowledge across sessions:** Maintain shared documentation, progress notes, and records of failed approaches.
- **Make feedback efficient:** Provide concise error summaries, searchable logs, fast test subsets, and periodic progress updates.
- **Assign complementary goals:** Give agents distinct responsibilities.

```
appuser@6a2fdd602d4b: /workspace/code
Finished 'release' profile [optimized] target(s) in 12.72s
appuser@6a2fdd602d4b: /workspace/code$ mkdir -p /workspace/code/.cargo
appuser@6a2fdd602d4b: /workspace/code$ echo -e '[target.riscv64gc-unknown-linux-musl]
linker = "riscv64-linux-gnu-gcc"' > /workspace/code/.cargo/config.toml
appuser@6a2fdd602d4b: /workspace/code$ RUSTFLAGS="-C target-feature=+crt-static" cargo build --release --target riscv64gc-unknown-linux-musl
warning: file '/workspace/code/src/main.rs' found to be present in multiple build targets:
* 'bin' target 'ccc'
* 'bin' target 'ccc-arm'
* 'bin' target 'ccc-i686'
* 'bin' target 'ccc-riscv'
* 'bin' target 'ccc-x86'
Compiling ccc v0.1.0 (/workspace/code)
Finished 'release' profile [optimized] target(s) in 12.85s
appuser@6a2fdd602d4b: /workspace/code$ cp -r /deps/linux-6.9 /tmp && cd /tmp/linux-6.9
appuser@6a2fdd602d4b: /tmp/linux-6.9$ mkdir -p /tmp/gcc-rootfs
cd /tmp/gcc-rootfs
tar -xzf /deps/riscv-gcc-rootfs.tar.gz
cd /tmp/linux-6.9
appuser@6a2fdd602d4b: /tmp/linux-6.9$ export CCC=/workspace/code/target/release/ccc-riscv
export CCx86=/workspace/code/target/release/ccc-x86
appuser@6a2fdd602d4b: /tmp/linux-6.9$ make ARCH=riscv CC=$CCC HOSTCC=$CCx86 CROSS_COMPILE=riscv64-linux-gnu- defconfig
HOSTCC scripts/basic/fixdep
HOSTCC scripts/kconfig/conf.o
HOSTCC scripts/kconfig/confdata.o
HOSTCC scripts/kconfig/expr.o
LEX scripts/kconfig/lexer.lex.c
YACC scripts/kconfig/parser.tab.[ch]
HOSTCC scripts/kconfig/lexer.lex.o
HOSTCC scripts/kconfig/menu.o
HOSTCC scripts/kconfig/parser.tab.o
HOSTCC scripts/kconfig/preprocess.o
HOSTCC scripts/kconfig/symbol.o
HOSTCC scripts/kconfig/util.o
HOSTLD scripts/kconfig/conf
*** Default configuration is based on 'defconfig'
#
# configuration written to .config
#
appuser@6a2fdd602d4b: /tmp/linux-6.9$
```



Summary

SAS vs MAS

Orchestration

Communication

Coordination

Failure Modes



Summary

- ✓ Single vs Multi-Agent Systems (MAS)
- ✓ MAS Orchestration Patterns
- ✓ Communication
- ✓ Shared State
- ✓ Failures and Challenges



See you **Wednesday** for
Optimization!

