

Analysis of Richardson-Lucy Deconvolution with a TV Prior

Jerald R. Evans

EE367 March 17, 2021

RL+TV_A
(*incorrect*)

$$\nabla \lambda \| \mathbf{Dx} \|_1 = \lambda \nabla \sum_{ij} \left(\sqrt{(\nabla_x \mathbf{x})_{ij}^2} + \sqrt{(\nabla_y \mathbf{x})_{ij}^2} \right) = -\lambda \left(\frac{\mathbf{D}_x \mathbf{x}}{|\mathbf{D}_x \mathbf{x}|} + \frac{\mathbf{D}_y \mathbf{x}}{|\mathbf{D}_y \mathbf{x}|} \right)$$

$$\mathbf{x}^{(q+1)} = \frac{\mathbf{A}^T \left(\frac{\mathbf{b}}{\mathbf{Ax}} \right)}{\mathbf{A}^T \mathbf{1} - \lambda \left(\frac{\mathbf{D}_x \mathbf{x}}{|\mathbf{D}_x \mathbf{x}|} + \frac{\mathbf{D}_y \mathbf{x}}{|\mathbf{D}_y \mathbf{x}|} \right)} \cdot \mathbf{x}^{(q)}$$


RL+TV_B
(*correct*)

$$\nabla \lambda \| \mathbf{Dx} \|_1 = \lambda \nabla \sum_{ij} \left(\sqrt{(\nabla_x \mathbf{x})_{ij}^2} + \sqrt{(\nabla_y \mathbf{x})_{ij}^2} \right) = \lambda \left(\mathbf{D}_x^T \frac{\mathbf{D}_x \mathbf{x}}{|\mathbf{D}_x \mathbf{x}|} + \mathbf{D}_y^T \frac{\mathbf{D}_y \mathbf{x}}{|\mathbf{D}_y \mathbf{x}|} \right)$$


$$\mathbf{x}^{(q+1)} = \frac{\mathbf{A}^T \left(\frac{\mathbf{b}}{\mathbf{Ax}} \right)}{\mathbf{A}^T \mathbf{1} + \lambda \left(\mathbf{D}_x^T \frac{\mathbf{D}_x \mathbf{x}}{|\mathbf{D}_x \mathbf{x}|} + \mathbf{D}_y^T \frac{\mathbf{D}_y \mathbf{x}}{|\mathbf{D}_y \mathbf{x}|} \right)} \cdot \mathbf{x}^{(q)}$$

Gradient Magnitude, 100 iterations, $\lambda=0.04$


Ground Truth Image



RL+TV_A




RL+TV_B




$$\mathbf{A}^T \mathbf{1} - \lambda \left(\frac{\mathbf{D}_x \mathbf{x}}{|\mathbf{D}_x \mathbf{x}|} + \frac{\mathbf{D}_y \mathbf{x}}{|\mathbf{D}_y \mathbf{x}|} \right)$$

Rule A Denom RL+TV_A $\lambda=0.04$, Iteration 35






$$\mathbf{A}^T \mathbf{1} + \lambda \left(\mathbf{D}_x^T \frac{\mathbf{D}_x \mathbf{x}}{|\mathbf{D}_x \mathbf{x}|} + \mathbf{D}_y^T \frac{\mathbf{D}_y \mathbf{x}}{|\mathbf{D}_y \mathbf{x}|} \right)$$

Rule B Denom RL+TV_B $\lambda=0.04$, Iteration 35




Comparison of RL+TV_A, $\lambda=0.04$ & RL+TV_B, $\lambda=0.02$




Gradient Magnitude, 200 iterations



RL+TV_A, $\lambda=0.04$













RL+TV_B, $\lambda=0.02$



Use Standard Deviation of Gradient Histogram as Measure of Sparsity







Conclusions

- For all images and the range of λ tested, at the optimal per image λ
 - RL+TV_A produces sparser gradients by all three measures
 - RL+TV_B produces higher log likelihood
 - RL+TV_B usually produces lower MSE

References

1. Gordon Wetzstein, EE 367 / CS 448I Computational Imaging and Display Notes: Noise, Denoising, and Image Reconstruction with Noise (lecture 10) http://stanford.edu/class/ee367/reading/lecture10_notes.pdf
2. Dey, N., Blanc-Feraud, L., Zimmer, C., Kam, Z., Olivo-Marin, J.-C., AND Zerubia, J. 2004. 3d microscopy deconvolution using Richardson-Lucy algorithm with total variation regularization. INRIA Technical Report.
3. Dey, N., Blanc-Feraud, L., Zimmer, C., Kam, Z., Olivo-Marin, J.-C., AND Zerubia, J. 2004. A deconvolution method for confocal microscopy with total variation regularization. In IEEE Symposium on Biomedical Imaging: Nano to Macro, 1223–1226.